

Title (en)
ELEVATOR HOIST DEVICE

Title (de)
AUFZUGSSEILVORRICHTUNG

Title (fr)
DISPOSITIF DE TREUIL POUR ASCENSEUR

Publication
EP 2322464 A1 20110518 (EN)

Application
EP 09805055 A 20090807

Priority

- JP 2009064028 W 20090807
- JP 2008205092 A 20080808

Abstract (en)

[Problem] A conventional hoist apparatus having a cantilever structure requires the use of a thick shaft of a larger shaft diameter when a sheave width and a sheave load are great. [Means for solution] An elevator hoist apparatus 1 includes a stator 4 formed by attaching a stator core 3 to an internal periphery of a frame 2, a rotor 11 formed by supporting a shaft with a rotor core, rotatably, by first and second bearings 7, 8, on first and second brackets 9, 10 provided in the frame 2, and a sheave 12 mounted on a projecting end portion of the shaft 6 projecting to an outer side of the first bearing 7. The sheave 12 includes a wire rope wind-up surface 14 which is formed on an external peripheral side of the sheave 12 and which includes a plurality of wire rope grooves 13 arranged in a row. The sheave 12 further includes a bearing insertion portion 15 which is formed on an internal peripheral side of the wire rope wind-up surface 14 and which is arranged to receive the first bearing 7. The first bearing 7 is inserted in the bearing insertion portion 15.

IPC 8 full level
B66B 11/08 (2006.01); **B66B 11/04** (2006.01)

CPC (source: EP KR)
B66B 11/0438 (2013.01 - EP); **B66B 11/08** (2013.01 - KR)

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

Designated extension state (EPC)
AL BA RS

DOCDB simple family (publication)

EP 2322464 A1 20110518; EP 2322464 A4 20141224; EP 2322464 B1 20170621; CN 102112387 A 20110629; CN 102112387 B 20141203;
JP 2010037094 A 20100218; JP 5347365 B2 20131120; KR 101208904 B1 20121206; KR 20110039486 A 20110418;
WO 2010016573 A1 20100211

DOCDB simple family (application)

EP 09805055 A 20090807; CN 200980130659 A 20090807; JP 2008205092 A 20080808; JP 2009064028 W 20090807;
KR 20117005013 A 20090807