

Title (en)

BACK-VENTILATED FIRE-RESISTANT WALL, IN PARTICULAR FOR A COMBUSTION FURNACE

Title (de)

HINTERLÜFTETE FEUERFESTE WAND, INSBESONDERE FÜR EINEN VERBRENNUNGSOFEN

Title (fr)

PAROI RÉFRACTAIRE VENTILÉE PAR L'ARRIÈRE, EN PARTICULIER POUR UN FOUR À COMBUSTION

Publication

EP 2326879 A2 20110601 (DE)

Application

EP 09775765 A 20090821

Priority

- CH 2009000277 W 20090821
- CH 13622008 A 20080826

Abstract (en)

[origin: WO2010022523A2] A fire-resistant wall intended in particular for use in a combustion furnace comprises a tube wall (1), composed of tubes (11) connected by webs (12), and, placed in front at a distance from the tube wall, a fire-resistant protective cladding (2) composed of a plurality of fire-resistant panels (21) which are arranged next to and above one another and which are fastened to the webs (12) of the tube wall via in each case at least one panel holder (22). The panels (21) are provided with continuous open grooves (21a) into which the panel holders (22) engage. In the tube wall (1) are provided inlet openings (31) via which air can be introduced into the gap (3) between the tube wall (1) and the protective cladding (2). Also provided are outlet openings through which air can be removed from the wall. The air supply openings (31) are arranged in the region of the open grooves (21a) of the panels (21), with the result that the supplied air flows directly into the grooves and is distributed through these grooves over the entire wall. By incorporating the grooves (21a) into the air distribution system within the wall, the gap width (d) between the tube wall (1) and the protective cladding (2) can be reduced to £ 5 mm, thereby considerably improving the heat transfer. It is possible at the same time to manage with relatively small air volumes and the pressure loss is considerably reduced, making it possible to achieve considerable energy savings.

IPC 8 full level

F23M 5/04 (2006.01); **F23M 5/08** (2006.01)

CPC (source: EP US)

F23M 5/04 (2013.01 - EP US); **F23M 5/085** (2013.01 - EP US); **F23M 2900/05001** (2013.01 - EP US)

Citation (search report)

See references of WO 2010022523A2

Cited by

CN109974026A

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

Designated extension state (EPC)

AL BA RS

DOCDB simple family (publication)

CH 699406 A2 20100226; DK 2326879 T3 20170116; EP 2326879 A2 20110601; EP 2326879 B1 20160921; ES 2606727 T3 20170327; JP 2012500957 A 20120112; JP 5530442 B2 20140625; PL 2326879 T3 20170331; PT 2326879 T 20161227; US 2011146596 A1 20110623; WO 2010022523 A2 20100304; WO 2010022523 A3 20100422

DOCDB simple family (application)

CH 13622008 A 20080826; CH 2009000277 W 20090821; DK 09775765 T 20090821; EP 09775765 A 20090821; ES 09775765 T 20090821; JP 2011524156 A 20090821; PL 09775765 T 20090821; PT 09775765 T 20090821; US 201113035820 A 20110225