

Title (en)
FLAT SEAL

Title (de)
FLACHDICHTUNG

Title (fr)
JOINT PLAT

Publication
EP 2329169 A1 20110608 (DE)

Application
EP 09765451 A 20090619

Priority
• DE 2009000842 W 20090619
• DE 102008029543 A 20080621

Abstract (en)
[origin: WO2009152815A1] The invention relates to a flat seal, in particular a cylinder head gasket or an exhaust flange seal, comprising at least one layer (1) provided with at least one through opening (2). Said through opening receives at least one elastically deformable profiled body (3) configured as an annular profile wire, having a defined material thickness. The total height of the non-deformed profiled body is greater than the thickness of the layer, and said layer is provided at least partially with material thickening (7, 7', 8, 8') in the region of the profiled body and/or outside of the profiled body.

IPC 8 full level
F16J 15/08 (2006.01)

CPC (source: EP US)
F16J 15/0818 (2013.01 - EP US); **F16J 15/0825** (2013.01 - EP US); **F16J 15/123** (2013.01 - EP US); **F16J 2015/0856** (2013.01 - EP US);
F16J 2015/0862 (2013.01 - EP US)

Citation (search report)
See references of WO 2009152815A1

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK TR

Designated extension state (EPC)
AL BA RS

DOCDB simple family (publication)
WO 2009152815 A1 20091223; CN 101910689 A 20101208; EP 2329169 A1 20110608; JP 2011525227 A 20110915;
US 2011101626 A1 20110505

DOCDB simple family (application)
DE 2009000842 W 20090619; CN 200980101727 A 20090619; EP 09765451 A 20090619; JP 2011513868 A 20090619;
US 200913000507 A 20090619