

Title (en)

SPARK PLUG FOR INTERNAL COMBUSTION ENGINE

Title (de)

ZÜNDKERZE FÜR EINEN VERBRENNUNGSMOTOR

Title (fr)

BOUGIE POUR MOTEUR A COMBUSTION INTERNE

Publication

**EP 2333918 A4 20140212 (EN)**

Application

**EP 09817648 A 20090915**

Priority

- JP 2009066078 W 20090915
- JP 2008253955 A 20080930

Abstract (en)

[origin: EP2333918A1] A spark plug without any noble metal chip on a ground electrode and capable of enhancing the ignition property, prolonging the life and ensuring a sufficiently high strength of the ground electrode is provided. The spark plug 1 includes a center electrode 5, an insulator 2, a metal shell 3, and a ground electrode 27. Spark discharge is provided substantially along a direction of an axis CL1 of the spark plug in a spark discharge gap 33 defined between the center electrode 5 and the ground electrode 27. The ground electrode includes a narrowed width portion 42 which has a substantially uniform width smaller than an outer diameter of a tip end surface 5F of the center electrode 5, and a widened width portion 41 having a width larger than the width of the narrowed width portion 42. When viewed from a tip end side of the spark plug in the direction of the axis CL1, a base end of the narrowed width portion 42 is located offset from the tip end surface 5F of the center electrode 5 toward the root side of the ground electrode 27. The base end of the narrowed width portion 42 is located offset from a center of the spark discharge gap toward the tip end side of the spark plug in the axial direction of the spark plug.

IPC 8 full level

**H01T 13/32** (2006.01); **H01T 13/20** (2006.01); **H01T 13/39** (2006.01)

CPC (source: EP KR US)

**H01T 13/20** (2013.01 - KR); **H01T 13/32** (2013.01 - EP KR US); **H01T 13/39** (2013.01 - EP US)

Citation (search report)

- [Y] JP S535629 U 19780119
- [Y] JP 2000252039 A 20000914 - NGK SPARK PLUG CO
- [Y] EP 0895327 A1 19990203 - NGK SPARK PLUG CO [JP]
- [Y] JP H07135066 A 19950523 - HONDA MOTOR CO LTD
- [YD] JP 2001307858 A 20011102 - NGK SPARK PLUG CO
- See references of WO 2010038611A1

Cited by

EP2814124A3

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

DOCDB simple family (publication)

**EP 2333918 A1 20110615; EP 2333918 A4 20140212; EP 2333918 B1 20170614;** CN 102165655 A 20110824; CN 102165655 B 20130821;  
JP 5331112 B2 20131030; JP WO2010038611 A1 20120301; KR 101238579 B1 20130228; KR 20110082024 A 20110715;  
US 2011175514 A1 20110721; US 8319409 B2 20121127; WO 2010038611 A1 20100408

DOCDB simple family (application)

**EP 09817648 A 20090915;** CN 200980138477 A 20090915; JP 2009066078 W 20090915; JP 2010515152 A 20090915;  
KR 20117009962 A 20090915; US 200913120089 A 20090915