

Title (en)

STORM DRAIN (GULLY), AND METHOD FOR OPERATING THE SAME

Title (de)

STRASSENEINLAUF (GULLY), SOWIE VERFAHREN ZUM BETRIEB DESSELBEN

Title (fr)

AVALOIR DE CHAUSSÉE (BOUCHE D'ÉGOUT) ET SON PROCÉDÉ DE FONCTIONNEMENT

Publication

EP 2337902 A1 20110629 (DE)

Application

EP 08874983 A 20081022

Priority

EP 2008008910 W 20081022

Abstract (en)

[origin: WO2010045953A1] The invention relates to a storm drain (gully) and to a method for operating the same, having an upper inlet chamber and a lower outlet chamber separated therefrom by means of an inlet chamber floor, wherein the outlet opening of the inlet chamber is through a pipe or a siphon lying at a significant distance above the inlet chamber floor, and having an outlet pipeline in the outlet chamber that can be closed by means of a float. In order to achieve a significantly improved function and also prevent an overflow, the invention proposes that a bypass (20) is provided through which excess discharge water can flow in case of overload, the upper end thereof opening into the inlet chamber (5) above the outlet opening (8) of the inlet chamber (5), and the lower end (22) thereof opening into the outlet pipeline (12) below the valve (13, 14).

IPC 8 full level

E03F 5/04 (2006.01); **E03F 5/16** (2006.01)

CPC (source: EP)

E03F 5/0401 (2013.01); **E03F 5/16** (2013.01)

Citation (search report)

See references of WO 2010045953A1

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MT NL NO PL PT RO SE SI SK TR

Designated extension state (EPC)

AL BA MK RS

DOCDB simple family (publication)

DE 202008017663 U1 20100401; EP 2337902 A1 20110629; EP 2337902 B1 20151014; WO 2010045953 A1 20100429

DOCDB simple family (application)

DE 202008017663 U 20081022; EP 08874983 A 20081022; EP 2008008910 W 20081022