

Title (en)

Wire break repairing device for wire-cut electric discharge machine

Title (de)

Drahtunterbrechungsreparaturvorrichtung für eine drahtgeschnittene elektrische Entladungsmaschine

Title (fr)

Dispositif de réparation de fils cassés pour machine à décharge électrique à coupe-pâte

Publication

**EP 2340907 B1 20161123 (EN)**

Application

**EP 10178112 A 20100921**

Priority

JP 2010000078 A 20100104

Abstract (en)

[origin: EP2340907A2] If a wire electrode breaks during electric discharge machining by a wire-cut electric discharge machine, the wire electrode is moved to the most recently machined one, from among the points of intersection at which the machining route intersects a circle with a predetermined radius (radius equal to or larger than the radius of the aperture of the nozzle on the wire guide) centered at the point of break of the wire electrode, and is automatically connected at the most recently machined point of intersection.

IPC 8 full level

**B23H 7/06** (2006.01); **B23H 7/10** (2006.01)

CPC (source: EP)

**B23H 7/065** (2013.01); **B23H 7/102** (2013.01)

Cited by

EP2959999A1; EP2952280A1; US10500660B2; US10503147B2; US10189101B2

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

DOCDB simple family (publication)

**EP 2340907 A2 20110706; EP 2340907 A3 20111221; EP 2340907 B1 20161123**; CN 102114560 A 20110706; JP 2011136409 A 20110714; JP 4904405 B2 20120328; KR 101199810 B1 20121109; KR 20110080117 A 20110712; TW 201139020 A 20111116; TW I450782 B 20140901

DOCDB simple family (application)

**EP 10178112 A 20100921**; CN 201010518573 A 20101020; JP 2010000078 A 20100104; KR 20100093779 A 20100928; TW 99134742 A 20101012