

Title (en)
Device and method for mixing dispersions and gases

Title (de)
Vorrichtung und Verfahren zum Mischen von Dispersionen und Gasen

Title (fr)
Dispositif et procédé destiné à mélanger des dispersions et des gaz

Publication
EP 2353705 A1 20110810 (DE)

Application
EP 10001079 A 20100203

Priority
EP 10001079 A 20100203

Abstract (en)
The device for mixing a dispersion with a gas, comprises an outer reception (2) and/or two perforated plates (3) arranged to each other by a spacer (4) spaced apart into the reception, which comprises a support for receiving a first perforated plate on which the first perforated plate is loosely arranged and the perforated plate of the spacer is loosely arranged on which the second perforated plate is arranged. The reception comprises a tapered section at its inlet- and/or outlet side (5, 6). The cross section rejuvenates itself at the inlet and/or outlet side around 10 %. The device for mixing a dispersion with a gas, comprises an outer reception (2) and/or two perforated plates (3) arranged to each other by a spacer (4) spaced apart into the reception, which comprises a support for receiving a first perforated plate on which the first perforated plate is loosely arranged and the perforated plate of the spacer is loosely arranged on which the second perforated plate is arranged. The reception comprises a tapered section at its inlet- and/or outlet side (5, 6). The cross section rejuvenates itself at the inlet and/or outlet side around 10 % in comparison to the average cross section of the reception. The perforated plates comprise a total hole surface per hole between 1-15% of the total hole surface, and have a thickness between 1 mm and 10 mm. The distance corresponds between the perforated plates of the 5 to 100-fold of the hole bottom thickness. The linear expansion of the device is conducted between the 5-fold and 50-fold of the diameter of the device, which has 3 and 100 perforated plates. An independent claim is included for a method for mixing a dispersion with a gas.

Abstract (de)
Die vorliegende Erfindung betrifft eine Vorrichtung sowie ein Verfahren zum Mischen einer Dispersion mit einem Gas, insbesondere einer Polymerdispersion mit einer gasförmigen Säure. Erfindungsgemäß wird eine Vorrichtung angegeben, welche aus einer äußeren Aufnahme (2) sowie wenigstens zwei mittels eines Abstandhalters (4) in der Aufnahme (2) zueinander beabstandet angeordnete Lochböden (3) aufweist, wobei die Aufnahme ein Auflager zur Aufnahme eines ersten Lochbodens aufweist, auf welchem ein Lochboden lose angeordnet ist und auf diesem ersten Lochboden der Abstandhalter lose angeordnet ist, auf welchem wiederum der zweite Lochboden angeordnet ist.

IPC 8 full level
B01F 3/04 (2006.01); **B01F 5/06** (2006.01); **B01J 10/00** (2006.01); **B01J 19/24** (2006.01)

CPC (source: EP)
B01F 23/2322 (2022.01); **B01F 25/45** (2022.01); **B01F 25/4521** (2022.01)

Citation (search report)

- [XAI] JP 2006198557 A 20060803 - SATO KOGYO
- [XAI] EP 0285725 A2 19881012 - CHUGOKU KAYAKU [JP]
- [A] WO 2006134401 A1 20061221 - JOHNSON MATTHEY PLC [GB], et al
- [A] US 2002060950 A1 20020523 - FURUKAWA HIDEO [JP]
- [A] US 3582048 A 19710601 - SAREM AMIR M

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

Designated extension state (EPC)
AL BA RS

DOCDB simple family (publication)
EP 2353705 A1 20110810; EP 2531283 A1 20121212; EP 2531283 B1 20160427; TW 201143883 A 20111216; WO 2011095454 A1 20110811

DOCDB simple family (application)
EP 10001079 A 20100203; EP 11702438 A 20110131; EP 2011051309 W 20110131; TW 100103808 A 20110201