

Title (en)
METHOD OF SWITCHING OPTICAL PATH, AND APPARATUS THEREOF

Title (de)
VERFAHREN UND VORRICHTUNG FÜR STRAHLENGANGWECHSEL

Title (fr)
PROCÉDÉ DE COMMUTATION D'UN CHEMIN OPTIQUE ET APPAREIL ASSOCIÉ

Publication
EP 2360858 A4 20120725 (EN)

Application
EP 09830328 A 20091124

Priority

- JP 2009069806 W 20091124
- JP 2008308007 A 20081202
- JP 2009090454 A 20090402
- JP 2009090455 A 20090402

Abstract (en)
[origin: EP2360858A1] Terminals of upstream and downstream sides of an in-service line and a detour line are connected by optical couplers. An optical oscilloscope is connected to one optical coupler, and a chirped pulse light source is connected to the other optical coupler to thereby form dualized lines. The detour line includes an optical line length adjuster for compensating for the phase difference of optical transmission signals that occurs because of the optical line length difference with the in-service line. Pulse light in which an optical frequency is chirped is transmitted from the chirped pulse light source. The pulse light is branched by the second optical coupler, passes through the in-service line and the detour line, is multiplexed again by the first optical coupler, and is measured by the optical oscilloscope. While matching an arrival time of the pulse light, the optical line length is adjusted by the optical line length adjuster so as to minimize the size of upper and lower limits of an interference waveform generated in an upper part of the pulse light waveform or so as to make a frequency of an interference waveform become zero.

IPC 8 full level
H04B 1/74 (2006.01); **H04B 10/02** (2006.01); **H04B 10/032** (2013.01); **H04B 10/12** (2006.01); **H04B 10/13** (2006.01); **H04B 10/135** (2006.01); **H04B 10/14** (2006.01); **H04B 10/20** (2006.01)

CPC (source: EP US)
H04B 10/032 (2013.01 - EP US); **H04J 14/02** (2013.01 - EP US); **H04J 14/0221** (2013.01 - EP US); **H04J 14/0294** (2013.01 - EP US); **H04J 14/0295** (2013.01 - EP US); **H04Q 11/0005** (2013.01 - EP US); **H04Q 11/0062** (2013.01 - EP US); **H04J 14/002** (2013.01 - EP US); **H04Q 2011/0043** (2013.01 - EP US); **H04Q 2011/0081** (2013.01 - EP US)

Citation (search report)

- [Y] JP 2007294565 A 20071108 - MITSUBISHI ELECTRIC CORP
- [A] JP H0961298 A 19970307 - NIPPON TELEGRAPH & TELEPHONE
- [XP] TANAKA K ET AL: "Frame-loss-free line switching method for in-service optical access network using interferometry line length measurement", OPTICAL FIBER COMMUNICATION - INCLUDES POST DEADLINE PAPERS, 2009. OFC 2009. CONFERENCE ON, IEEE, PISCATAWAY, NJ, USA, 22 March 2009 (2009-03-22), pages 1 - 3, XP031468157, ISBN: 978-1-4244-2606-5
- [Y] YUJI AZUMA ET AL: "Hikari Access Baitai Kirikae Hoshiki no Kiso Kento: Service Mushundan Hikari Baitai Kirikae System", DENSHI JOUHO TSUUSHIN GAKKAI GIJUTSU KENKYUU HOUKOKU // INSTITUTE OF ELECTRONICS, INFORMATION AND COMMUNICATION ENGINEERS. TECHNICAL REPORT, DENSHI JOUHO TSUUSHIN GAKKAI, JP, vol. 108, no. 310, 13 November 2008 (2008-11-13), pages 27 - 31, XP008151272, ISSN: 0913-5685
- See references of WO 2010064561A1

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

DOCDB simple family (publication)
EP 2360858 A1 20110824; **EP 2360858 A4 20120725**; **EP 2360858 B1 20130619**; CN 102227885 A 20111026; CN 102227885 B 20140326; JP 5115995 B2 20130109; JP WO2010064561 A1 20120510; US 2011236015 A1 20110929; US 8718467 B2 20140506; WO 2010064561 A1 20100610

DOCDB simple family (application)
EP 09830328 A 20091124; CN 200980147191 A 20091124; JP 2009069806 W 20091124; JP 2010541299 A 20091124; US 200913130108 A 20091124