

Title (en)

Hearing aid with frequency shift and accompanying method

Title (de)

Hörgerät mit Frequenzverschiebung und zugehöriges Verfahren

Title (fr)

Appareil auditif avec décalage de fréquence et procédé correspondant

Publication

EP 2360945 A3 20130710 (DE)

Application

EP 10187394 A 20101013

Priority

- DE 102010006154 A 20100129
- US 29937010 P 20100129

Abstract (en)

[origin: EP2360945A2] The hearing aid (1) has a low pass filter (18) e.g. elliptic filter, characterized by a cut-off frequency and uncoupling a low pass output signal (105) from an output signal (103) of a signal processing unit (3). A high pass filter (19) is characterized by another cut-off frequency signal and uncouples a high-pass output signal (104) from the output signal of the processing unit. A frequency shift unit changes frequency of the high-pass output signal to high frequencies. A preset spacing is provided between the two cut-off frequencies, where the spacing ranges between 20 to 50 hertz. An independent claim is also included for a method for shifting frequency in a hearing aid.

IPC 8 full level

H04R 25/00 (2006.01)

CPC (source: EP US)

H04R 25/353 (2013.01 - EP US); **H04R 25/453** (2013.01 - EP US)

Citation (search report)

- [A] WO 2009143898 A1 20091203 - PHONAK AG [CH], et al
- [A] EP 1480494 A2 20041124 - PHONAK AG [CH]
- [A] EP 1401242 A2 20040324 - SIEMENS AUDIOLOGISCHE TECHNIK [DE]

Cited by

US9179222B2; US9794698B2

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

DOCDB simple family (publication)

EP 2360945 A2 20110824; EP 2360945 A3 20130710; EP 2360945 B1 20140910; DE 102010006154 A1 20110804;
DE 102010006154 B4 20120119; DK 2360945 T3 20141215; US 2011194714 A1 20110811; US 8538053 B2 20130917

DOCDB simple family (application)

EP 10187394 A 20101013; DE 102010006154 A 20100129; DK 10187394 T 20101013; US 201113016422 A 20110128