

Title (en)

LIGHTNING DEVICE WITH PROTECTING COVER

Title (de)

BELEUCHTUNGSVORRICHTUNG MIT SCHUTZABDECKUNG

Title (fr)

DISPOSITIF D'ÉCLAIRAGE AVEC COUVERTURE DE PROTECTION

Publication

EP 2368068 A1 20110928 (EN)

Application

EP 09833736 A 20091215

Priority

- SE 2009051423 W 20091215
- SE 0850139 A 20081215

Abstract (en)

[origin: WO2010071573A1] The present invention relates to a lighting device comprising an elongated cold cathode tube (3), which cold cathode tube has a first and a second end (10, 11) and a first (6) and a second (9) conducting wire, connected to the cold cathode tube on the first and the second end respectively, for connecting the cold cathode tube to a current or voltage source, which device further comprises an at least partially transparent tube (2) having a first and a second tube end (7, 8) for the enclosing reception of the cold cathode tube, in which the said tube is configured in one piece, which forms a radially- enclosed conducting wire channel (5) arranged to receive the first conducting wire of the cold cathode tube, and a light source channel (4) arranged to receive the cold cathode tube, which channels extend between the first tube end and the second tube end.

IPC 8 full level

F21V 15/01 (2006.01); **F21V 15/015** (2006.01); **H01J 61/04** (2006.01); **H01J 61/36** (2006.01)

CPC (source: EP US)

F21V 3/02 (2013.01 - EP US); **F21V 15/01** (2013.01 - EP); **F21Y 2103/00** (2013.01 - EP US); **H01J 61/78** (2013.01 - EP)

Citation (search report)

See references of WO 2010071573A1

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

DOCDB simple family (publication)

WO 2010071573 A1 20100624; EP 2368068 A1 20110928; RU 2011126079 A 20130120; RU 2518450 C2 20140610

DOCDB simple family (application)

SE 2009051423 W 20091215; EP 09833736 A 20091215; RU 2011126079 A 20091215