

Title (en)

DEVICE FOR THE SELECTIVE GRANULOMETRIC SEPARATION OF SOLID POWDERY MATERIALS USING CENTRIFUGAL ACTION, AND METHOD FOR USING SUCH A DEVICE

Title (de)

VORRICHTUNG ZUR SELEKTIVEN GRANULOMETRISCHEN TRENNUNG VON FESTPULVERMATERIALIEN MITHILFE EINER ZENTRIFUGALOPERATION SOWIE VERFAHREN ZUR VERWENDUNG EINER SOLCHEN VORRICHTUNG

Title (fr)

DISPOSITIF DE SÉPARATION GRANULOMÉTRIQUE SÉLECTIVE DE MATIÈRES PULVÉRULENTES SOLIDES, À ACTION CENTRIFUGE, ET PROCÉDÉ D'UTILISATION D'UN TEL DISPOSITIF

Publication

**EP 2382056 B1 20140723 (FR)**

Application

**EP 10705898 A 20100126**

Priority

- FR 2010000065 W 20100126
- FR 0900378 A 20090129

Abstract (en)

[origin: CA2750690A1] The invention relates to a device for the selective granulometric separation of solid powdery materials using centrifugal action, capable of separating materials into two fractions, i.e. a fine material fraction and a coarse material fraction, including: a housing (6), a cylindrical rotor (2) which is rotatable, relative to said housing, about a vertical axis inside said housing and provided with blades (3) evenly distributed on the periphery of an upper outlet opening through which a stream of gas, laden with particles having a size lower than a predetermined particle size, is drawn, a set of vertical adjustable vanes evenly distributed about the rotor along the generatrices of a virtual cylinder and directing the gas stream towards the rotor, means for feeding the particles between the vanes and the rotor, collecting means lower than the rotor for collecting the unfed particles having fallen and having a size larger than the predetermined particle size. According to the invention, said collecting means includes a peripheral system with a fluidised bed, wherein the bed extends about the rotor axis, at least underneath said vanes and the gap between the vanes (7) and the rotor (2), the speed of the fluidisation gas in a horizontal section of the fluidised bed being lower than 1 m/s so as to induce another separation of the fine materials and of the coarse materials in which said fine materials are fed back into the gap between said areas and said rotor.

IPC 8 full level

**B07B 11/06** (2006.01); **B07B 4/04** (2006.01); **B07B 7/083** (2006.01)

CPC (source: EP US)

**B07B 4/04** (2013.01 - EP US); **B07B 7/083** (2013.01 - EP US); **B07B 11/06** (2013.01 - EP US)

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

DOCDB simple family (publication)

**FR 2941389 A1 20100730; FR 2941389 B1 20111014;** CA 2750690 A1 20100805; CN 102300647 A 20111228; CN 102300647 B 20131225; DK 2382056 T3 20140908; EP 2382056 A1 20111102; EP 2382056 B1 20140723; ES 2496716 T3 20140919; JP 2012516231 A 20120719; JP 5735925 B2 20150617; MX 2011007809 A 20110921; PL 2382056 T3 20141231; RU 2011135816 A 20130310; RU 2513701 C2 20140420; UA 102875 C2 20130827; US 2011281713 A1 20111117; US 9022222 B2 20150505; WO 2010086528 A1 20100805

DOCDB simple family (application)

**FR 0900378 A 20090129;** CA 2750690 A 20100126; CN 201080005797 A 20100126; DK 10705898 T 20100126; EP 10705898 A 20100126; ES 10705898 T 20100126; FR 2010000065 W 20100126; JP 2011546905 A 20100126; MX 2011007809 A 20100126; PL 10705898 T 20100126; RU 2011135816 A 20100126; UA A201109501 A 20100126; US 201013145886 A 20100126