

Title (en)
ELEVATOR DEVICE

Title (de)
AUFZUGSVORRICHTUNG

Title (fr)
DISPOSITIF D'ASCENSEUR

Publication
EP 2383216 A1 20111102 (EN)

Application
EP 09839159 A 20090128

Priority
JP 2009051337 W 20090128

Abstract (en)

In an elevator apparatus, a car is moved inside a hoistway. A speed governor includes: a rotating shaft that rotates in response to movement of the car; a centrifugal weight that revolves around the rotating shaft together with the rotation of the rotating shaft; an extensible arm that links the centrifugal weight to the rotating shaft, and that is displaced relative to the rotating shaft in response to a centrifugal force to which the centrifugal weight is subjected due to the revolution; and a displacement setting apparatus that extends and retracts the extensible arm to set a length of the extensible arm to different lengths during normal rotation and during reverse rotation of the rotating shaft. The speed governor detects presence or absence of an abnormality in a speed of the car based on the displacement of the extensible arm relative to the rotating shaft.

IPC 8 full level
B66B 5/04 (2006.01)

CPC (source: EP KR)
B66B 5/04 (2013.01 - KR); **B66B 5/044** (2013.01 - EP)

Citation (search report)
See references of WO 2010086967A1

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK TR

DOCDB simple family (publication)
EP 2383216 A1 20111102; CN 102239100 A 20111109; JP WO2010086967 A1 20120726; KR 20110094139 A 20110819;
WO 2010086967 A1 20100805

DOCDB simple family (application)
EP 09839159 A 20090128; CN 200980148892 A 20090128; JP 2009051337 W 20090128; JP 2010548286 A 20090128;
KR 20117016055 A 20090128