

Title (en)
APPARATUS FOR THE SUSPENDED OR LYING DISPLAY OF ARTICLES

Title (de)
VORRICHTUNG ZUR HÄNGENDEN ODER LIEGENDEN PRÄSENTATION VON ARTIKELN

Title (fr)
DISPOSITIF POUR PRÉSENTER DES ARTICLES SUSPENDUS OU POSÉS À PLAT

Publication
EP 2391244 B1 20130703 (DE)

Application
EP 10702585 A 20100202

Priority
• CH 2010000025 W 20100202
• DE 202009001247 U 20090202

Abstract (en)
[origin: WO2010085907A1] The apparatus designed for the suspended or lying display of articles first comprises a plug-in sleeve (4), which at the front has an open shaft (42) extending into the interior of the plug-in sleeve (4). On the inside, the plug-in sleeve (4) has a locking contour (45), which is arranged as an elevation at the top in the shaft (42). The plug-in sleeve (4) is intended for fastening to a back side (91) of a supporting structure (9). The shaft (42) leads to a front side (90) of the supporting structure (9). The apparatus further comprises a carrier (1, 2), which has a plug part (10, 20) intended to be inserted into the shaft (42) with a rear edge (11, 21) first. The plug part (10, 20) has a flat cross-section and has a mating contour (12, 22), which is intended to engage with the locking contour (45) on the plug-in sleeve (4) and designed as a recess. The carrier is used to directly receive articles or to support a rack (3). The configuration of the plug part (10, 20) and plug-in sleeve (4) forces the insertion of the plug part (10, 20) into the plug-in sleeve (4) with the rear edge (11, 21) lowered. The engagement between the locking contour (45) and mating contour (12, 22) as a locked state is not achieved until the carrier (1, 2) is moved with an upwardly traveling rear edge (11, 21) of the plug part (10, 20). The locking contour (45) is arranged at the top center in the shaft (42) of the plug-in sleeve (4), while the mating contour (12, 22) is located axially centered in the plug part (10, 20). In the second version, the carrier (2) has a shaft (25), which connects to the plug part (20) and can be docked to a console (5) to which a rack (3) is fastened.

IPC 8 full level
A47B 96/06 (2006.01); **A47F 5/08** (2006.01)

CPC (source: EP US)
A47B 96/06 (2013.01 - EP US); **A47F 5/0807** (2013.01 - EP US); **A47F 5/0815** (2013.01 - EP US)

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

DOCDB simple family (publication)
DE 202009001247 U1 20090416; EP 2391244 A1 20111207; EP 2391244 B1 20130703; US 2011284486 A1 20111124;
WO 2010085907 A1 20100805

DOCDB simple family (application)
DE 202009001247 U 20090202; CH 2010000025 W 20100202; EP 10702585 A 20100202; US 201013146992 A 20100202