

Title (en)
NECKER INFEED

Title (de)
EINHALSVORRICHTUNGSZULAUF

Title (fr)
ALIMENTATION DE MACHINE À RÉTREINDRE

Publication
EP 2391466 A1 20111207 (EN)

Application
EP 09782357 A 20090828

Priority
• EP 2009061161 W 20090828
• GB 0816167 A 20080905

Abstract (en)
[origin: WO2010026115A1] An infeed assembly for introducing can bodies to necker tooling for reducing the diameter of an open end of the can body comprises three turrets: an infeed turret (30) which receives incoming can bodies from a chute, an infeed transfer turret (40) and a waxer turret (50). The infeed turret can have, for example 12 pockets for receiving the can bodies, which are then transferred to the infeed transfer turret which has 6 pockets. The important feature of the invention is that the transfer turret has the same number of pockets as are on the waxer turret, thereby avoid can damage when waxing rollers on the waxer turret engage an incoming can body.

IPC 8 full level
B21D 51/26 (2006.01)

CPC (source: EP)
B21D 51/2692 (2013.01)

Citation (search report)
See references of WO 2010026115A1

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

DOCDB simple family (publication)
WO 2010026115 A1 20100311; EP 2391466 A1 20111207; EP 2391466 B1 20160323; GB 0816167 D0 20081015

DOCDB simple family (application)
EP 2009061161 W 20090828; EP 09782357 A 20090828; GB 0816167 A 20080905