

Title (en)

METHOD AND DEVICE FOR HYDRODYNAMICALLY ELIMINATING DEFECTS IN THE INTERIOR OF PIPELINES

Title (de)

VERFAHREN UND VORRICHTUNG ZUM HYDRODYNAMISCHEN BESEITIGEN VON STÖRSTELLEN IM INNEREN VON ROHRLEITUNGEN

Title (fr)

PROCÉDÉ ET DISPOSITIF D'ÉLIMINATION HYDRODYNAMIQUE DE ZONES ENCRASSÉES DANS LA LUMIÈRE DE CONDUITES

Publication

EP 2393615 A2 20111214 (DE)

Application

EP 10707207 A 20100208

Priority

- EP 2010000768 W 20100208
- DE 102009007946 A 20090206

Abstract (en)

[origin: WO2010089146A2] The invention relates to a method and to a device for hydrodynamically treating defects in the interior of pipelines, in particular for reclaiming and cleaning water-bearing pipelines (1) in household and industrial areas. A pressure jet nozzle (5) is thereby pushed forward by means of a pushing bar (9) having a high compressive and tensile strength, until the defect in the pipeline (1) is reached. The pressure jet nozzle (5) can have working fluid applied thereto by means of a pressure hose (8) outside of the pipeline system. The pressure jet (7) impinging on the defect location with high kinetic energy thereby eliminates the defect.

IPC 8 full level

B08B 9/043 (2006.01); **E03B 7/00** (2006.01); **E03F 9/00** (2006.01)

CPC (source: EP)

B08B 9/0433 (2013.01); **E03B 7/006** (2013.01); **E03F 9/00** (2013.01)

Citation (search report)

See references of WO 2010089146A2

Cited by

EP3431197A2

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

DOCDB simple family (publication)

WO 2010089146 A2 20100812; WO 2010089146 A3 20111027; DE 102009007946 A1 20110317; DE 202010018297 U1 20150807; EP 2393615 A2 20111214; EP 2393615 B1 20160622

DOCDB simple family (application)

EP 2010000768 W 20100208; DE 102009007946 A 20090206; DE 202010018297 U 20100208; EP 10707207 A 20100208