

Title (en)

Arc chamber for a medium- or high-voltage circuit breaker with reduced operating energy

Title (de)

Unterbrechungskammer eines Schutzschralters für Hoch- und Mittelspannung mit reduzierter Bedienungsenergie

Title (fr)

Chambre de coupure pour disjoncteur à moyenne ou haute tension à énergie de manoeuvre réduite

Publication

EP 2402969 B1 20130529 (FR)

Application

EP 11172006 A 20110629

Priority

FR 1055323 A 20100701

Abstract (en)

[origin: EP2402969A1] The device has a pair of movable arc contacts (5, 6), and a compression chamber whose volume (V1) varies and opens in a blowing chamber under action of a blowing-piston (60). One of the arc contacts is indirectly linked to an operating rod by mechanical transmission units for obtaining a value of ratio of displacement speed of the movable arc contact and the operating rod greater than 1. The blowing chamber is integrated to the movable arc contact and a permanent arc contact (3), and a contact carrier tube (8) provides current to the permanent arc contact while movable arc contact is fixed.

IPC 8 full level

H01H 33/90 (2006.01)

CPC (source: EP)

H01H 33/90 (2013.01); **H01H 2033/028** (2013.01); **H01H 2033/907** (2013.01); **H01H 2033/908** (2013.01)

Cited by

CN112635230A; CN113782364A; AU2014210106B2; RU2619272C2; FR3038448A1; CN109346370A; EP2851919A1; CN104465201A; US9208966B2; WO2014114484A1; WO2015028349A1; US9460873B2

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

EP 2402969 A1 20120104; EP 2402969 B1 20130529; FR 2962252 A1 20120106; FR 2962252 B1 20130830

DOCDB simple family (application)

EP 11172006 A 20110629; FR 1055323 A 20100701