

Title (en)

VIBRATION SENSOR AND IN-LINE MEASURING DEVICE COMPRISING SAID SENSOR

Title (de)

MESSAUFNEHMER VOM VIBRATIONSTYP SOWIE IN-LINE-MESSGERÄT MIT EINEM SOLCHEN MESSAUFNEHMER

Title (fr)

CAPTEUR DE MESURE À VIBRATION ET INSTRUMENT DE MESURE EN LIGNE MUNI D'UN TEL CAPTEUR DE MESURE

Publication

**EP 2406591 A1 20120118 (DE)**

Application

**EP 10710822 A 20100311**

Priority

- EP 2010053125 W 20100311
- DE 102009001472 A 20090311
- DE 102009027580 A 20090709

Abstract (en)

[origin: WO2010103075A1] The measuring system according to the invention comprises a vibration-type measuring transducer, through which the medium flows during operation and which is intended to generate oscillation signals that are dependent on a viscosity of the flowing medium and/or on a Reynolds number of the flowing medium, and transducer electronics which are electrically coupled to the measuring transducer and are intended to drive the measuring transducer and to evaluate oscillation signals provided by the measuring transducer. The measuring transducer has an inlet-side flow divider (201) with at least two flow openings (201A, 201B) which are at a distance from one another, an outlet-side flow divider (202) with at least two flow openings (202A, 202B) which are at a distance from one another, at least two straight measuring tubes (181, 182) which are parallel to one another, are connected to the flow dividers (201, 202) so as to form a tube arrangement with at least two flow paths connected in parallel in terms of flow technology and are intended to guide flowing medium, and an electromechanical exciter arrangement (4) for exciting and maintaining mechanical oscillations of the at least two measuring tubes (181, 182). An inlet-side measuring tube end of each of the at least two measuring tubes opens into a flow opening (201A) of the inlet-side flow divider (201) and an outlet-side, second measuring tube end of each of said measuring tubes opens into a flow opening (202A) of the outlet-side flow divider (202). The transducer electronics use one of the electrical driver signals supplied to the exciter arrangement to feed electrical exciter power into the exciter arrangement, while the exciter arrangement at least proportionately converts electrical exciter power into mirror-image torsional oscillations of the at least two measuring tubes (181, 182).

IPC 8 full level

**G01F 1/84** (2006.01)

CPC (source: EP US)

**G01F 1/8409** (2013.01 - EP US); **G01F 1/8413** (2013.01 - EP US); **G01F 1/8431** (2013.01 - EP US); **G01F 1/8436** (2013.01 - EP US); **G01F 1/8495** (2013.01 - EP US); **G01F 15/024** (2013.01 - EP US); **G01N 11/16** (2013.01 - EP US)

Citation (search report)

See references of WO 2010103078A1

Citation (examination)

WO 9608697 A2 19960321 - SMITH METER INC [US], et al

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

DOCDB simple family (publication)

**WO 2010103075 A1 20100916**; CA 2754597 A1 20100916; CA 2754597 C 20140715; CA 2754682 A1 20100916; CA 2754682 C 20140722; CA 2754889 A1 20100916; CA 2754889 C 20140715; CN 102348961 A 20120208; CN 102348961 B 20150422; CN 102348962 A 20120208; CN 102348962 B 20151202; CN 102348963 A 20120208; CN 102348963 B 20150603; EP 2406589 A1 20120118; EP 2406589 B1 20210825; EP 2406590 A1 20120118; EP 2406590 B1 20201216; EP 2406591 A1 20120118; EP 2406593 A1 20120118; EP 2406594 A1 20120118; EP 2417425 A1 20120215; EP 2417425 B1 20190814; RU 2011141118 A 20130420; RU 2492430 C2 20130910; US 2010242623 A1 20100930; US 2010242624 A1 20100930; US 2010251830 A1 20101007; US 2011146383 A1 20110623; US 2011146416 A1 20110623; US 2011259123 A1 20111027; US 2013133436 A1 20130530; US 8316722 B2 20121127; US 8333119 B2 20121218; US 8333120 B2 20121218; US 8333121 B2 20121218; US 8336396 B2 20121225; US 8347736 B2 20130108; US 9052225 B2 20150609; WO 2010103076 A1 20100916; WO 2010103077 A1 20100916; WO 2010103078 A1 20100916; WO 2010103079 A1 20100916; WO 2010103080 A1 20100916

DOCDB simple family (application)

**EP 2010053122 W 20100311**; CA 2754597 A 20100311; CA 2754682 A 20100311; CA 2754889 A 20100311; CN 201080011575 A 20100311; CN 201080011637 A 20100311; CN 201080011859 A 20100311; EP 10707917 A 20100311; EP 10708530 A 20100311; EP 10709478 A 20100311; EP 10710822 A 20100311; EP 10711032 A 20100311; EP 10713150 A 20100311; EP 2010053123 W 20100311; EP 2010053124 W 20100311; EP 2010053125 W 20100311; EP 2010053126 W 20100311; EP 2010053127 W 20100311; RU 2011141118 A 20100311; US 201213682844 A 20121121; US 65953010 A 20100311; US 65953110 A 20100311; US 65953210 A 20100311; US 65953310 A 20100311; US 65953410 A 20100311; US 65953510 A 20100311