

Title (en)  
SIMPLIFIED CONDUCTOR FOR ELECTRICAL SWITCHGEAR AND ELECTRICAL SWITCHGEAR COMPRISING SUCH A CONDUCTOR

Title (de)  
VEREINFACHTER LEITER FÜR SCHALTGERÄT UND SCHALTGERÄT MIT EINEM SOLCHEN LEITER

Title (fr)  
CONDUCTEUR SIMPLIFIÉ POUR APPAREILLAGE ELECTRIQUE ET APPAREILLAGE ELECTRIQUE COMPORTANT AU MOINS UN TEL CONDUCTEUR

Publication  
**EP 2409310 A1 20120125 (FR)**

Application  
**EP 10709216 A 20100318**

Priority  
• EP 2010053517 W 20100318  
• FR 0951812 A 20090320

Abstract (en)  
[origin: WO2010106126A1] The invention relates to a conductor (2) for an electric apparatus that comprises a first electrically conductive bearing element (14) with a longitudinal axis and at least two electric contact elements (16.1, 16.2) to be brought into contact, the bearing element (14) having an recessed cylindrical shape with, on the outer periphery thereof, at least two housings (20, 21) for receiving said contact elements (16.1, 16.2), said housings (20, 21) being substantially symmetrically arranged, wherein the contact elements (16.1, 16.2) are retained in the housings (20, 21) by clamping. The conductor may form a mobile contact for a circuit-breaker.

IPC 8 full level  
**H01H 1/42** (2006.01); **H01H 31/02** (2006.01); **H01H 31/28** (2006.01)

CPC (source: EP)  
**H01H 31/026** (2013.01); **H01H 1/42** (2013.01); **H01H 31/28** (2013.01)

Citation (search report)  
See references of WO 2010106126A1

Designated contracting state (EPC)  
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

DOCDB simple family (publication)  
**WO 2010106126 A1 20100923**; CA 2754611 A1 20100923; CA 2754611 C 20180424; EP 2409310 A1 20120125; EP 2409310 B1 20150408; FR 2943451 A1 20100924; FR 2943451 B1 20121221

DOCDB simple family (application)  
**EP 2010053517 W 20100318**; CA 2754611 A 20100318; EP 10709216 A 20100318; FR 0951812 A 20090320