

Title (en)
AIR CONDITIONER

Title (de)
KLIMAANLAGE

Title (fr)
CLIMATISEUR

Publication
EP 2410262 A1 20120125 (EN)

Application
EP 10753301 A 20100318

Priority

- JP 2010001942 W 20100318
- JP 2009069132 A 20090319

Abstract (en)

To provide an air conditioning apparatus capable of quickly ensuring performance during startup and keeping post-startup overshooting to a minimum. An air conditioning apparatus (1) uses a refrigeration cycle which has a compressor (21) and a refrigerant tube (F) whose external periphery is composed of a magnetic tube (F2), the air conditioning apparatus (1) comprising a coil (68), a pressure sensor (29a), and a control part (11). The coil (68) generates a magnetic field for induction-heating the magnetic tube (F2). The pressure sensor (29a) detects refrigerant pressure in a high-pressure side of at least part of the refrigeration cycle. When the refrigeration cycle is performing an air-warming operation, the control part (11) initiates a state in which magnetic field generation by the coil (68) is at a maximum supplied electricity (Mmax) from the time the frequency of the compressor (21) is equal to or greater than a predetermined minimum frequency (Qmin), and the control part (11) performs this state until the pressure detected by the pressure sensor (29a) reaches a target high pressure (Ph). Onward from the time the target high pressure is reached, operation is performed under the restriction that a steady supplied electricity (M2) lower than the maximum supplied electricity (Mmax) is the upper output limit.

IPC 8 full level
F25B 1/00 (2006.01); **F24F 1/00** (2011.01); **F24F 11/02** (2006.01); **F25B 13/00** (2006.01); **F25B 47/02** (2006.01)

CPC (source: EP KR US)
F25B 13/00 (2013.01 - EP KR US); **F25B 47/022** (2013.01 - EP KR US); **F25B 2313/008** (2013.01 - EP KR US);
F25B 2313/02741 (2013.01 - EP KR US); **F25B 2313/0312** (2013.01 - EP KR US); **F25B 2313/0314** (2013.01 - EP KR US);
F25B 2313/0315 (2013.01 - EP KR US); **F25B 2400/01** (2013.01 - EP US); **F25B 2500/26** (2013.01 - EP KR US)

Citation (search report)
See references of WO 2010106805A1

Cited by
EP2581692A3; CN105571228A; EP3926244A4; US9217587B2

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

DOCDB simple family (publication)

EP 2410262 A1 20120125; AU 2010225944 A1 20111103; AU 2010225944 B2 20121115; CN 102348943 A 20120208;
JP 2010223459 A 20101007; JP 4826643 B2 20111130; KR 101233903 B1 20130215; KR 20110139288 A 20111228;
RU 2011142193 A 20130427; RU 2484390 C1 20130610; US 2012006040 A1 20120112; WO 2010106805 A1 20100923

DOCDB simple family (application)

EP 10753301 A 20100318; AU 2010225944 A 20100318; CN 201080012761 A 20100318; JP 2009069132 A 20090319;
JP 2010001942 W 20100318; KR 20117024510 A 20100318; RU 2011142193 A 20100318; US 201013256480 A 20100318