

Title (en)

Flat tie down point

Title (de)

Flacher Verzurrpunkt

Title (fr)

Point d'amarrage plat

Publication

EP 2412660 B1 20131120 (DE)

Application

EP 11169269 A 20110609

Priority

DE 102010032571 A 20100728

Abstract (en)

[origin: EP2412660A1] The device (1) has an eyelet (3) swivelably supported at a bracket body (2) around a swiveling axis. The bracket body is coupled with a bolt (6) at a fixation point. The bracket body is rotatably supported via two bearing sockets (5) around a rotation axis, where the swiveling axis and the rotation axis are arranged at a distance from each other in an angle. The bracket body is designed in a U-shape in cross section, and a filling body (4) is arranged in the eyelet. A bearing area is formed between the filling body and a valley area of the body for bearing the eyelet.

IPC 8 full level

B66C 1/66 (2006.01)

CPC (source: EP)

B66C 1/66 (2013.01)

Cited by

LU92242B1; CN103466433A; LU92243B1; US10131523B2; WO2015169673A1; WO2015004126A1; WO2015004124A1; WO2023149177A1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

EP 2412660 A1 20120201; EP 2412660 B1 20131120; DE 102010032571 A1 20120202

DOCDB simple family (application)

EP 11169269 A 20110609; DE 102010032571 A 20100728