

Title (en)

Apparatus for fabricating a glass rod and method of same

Title (de)

Vorrichtung zur Herstellung einer Glasstange und Verfahren dafür

Title (fr)

Appareil de fabrication d'une tige en verre et son procédé

Publication

**EP 2428495 B1 20190501 (EN)**

Application

**EP 11180370 A 20110907**

Priority

- JP 2010200504 A 20100908
- JP 2011194105 A 20110906

Abstract (en)

[origin: EP2428495A1] The present invention provides an apparatus and a method for fabricating a glass rod capable of suppressing a diameter fluctuation of a drawn glass rod even in case of a relatively large diameter reduction ratio between a glass preform and a glass rod, such as 60 to 95%. A feed speed V1 of the glass preform is set to a constant value, a diameter D of the glass preform is acquired for determining the drawing speed V2 from a measured diameter data of the glass preform before being drawn at a diameter acquisition position defined with respect to a reference position of the furnace, and a distance from the reference position to the diameter acquisition position is defined so as to vary depending on a diameter fluctuation of the glass preform before being drawn in a longitudinal direction thereof.

IPC 8 full level

**C03B 37/012** (2006.01)

CPC (source: EP US)

**C03B 37/01242** (2013.01 - EP US)

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

**EP 2428495 A1 20120314; EP 2428495 B1 20190501**; CN 102399058 A 20120404; JP 2012076989 A 20120419; JP 5576342 B2 20140820; US 2012055198 A1 20120308; US 8904825 B2 20141209

DOCDB simple family (application)

**EP 11180370 A 20110907**; CN 201110268775 A 20110908; JP 2011194105 A 20110906; US 201113226609 A 20110907