

Title (en)
HYDRAULIC VALVE DEVICE

Title (de)
HYDRAULISCHE VENTILVORRICHTUNG

Title (fr)
DISPOSITIF DE SOUPAPE HYDRAULIQUE

Publication
EP 2430319 A1 20120321 (DE)

Application
EP 10717055 A 20100423

Priority

- EP 2010002501 W 20100423
- DE 102009021103 A 20090513

Abstract (en)
[origin: WO2010130334A1] The invention relates to a hydraulic valve device (1) having a fluid connection arrangement (10) comprising a multiplicity of fluid connection points which can at least partially be actuated by means of a control device (18). As a result of the fact that, by way of a means (2) for measuring the load pressure, the control device (18) can be moved into a rapid traverse position when a maximum load pressure is exceeded in a power stroke position and vice versa, and that at least one fluid-conducting working chamber of a consumer (4) is connected to one of the use connections (A) during a switch of the control device (18) for a change from power stroke to rapid traverse, a jerk-free transition from a working stroke to a rapid traverse is attained and a homogeneous, jerk-free return to the working stroke is enabled when an overload situation is encountered in the rapid traverse.

IPC 8 full level
F15B 13/04 (2006.01)

CPC (source: EP US)
F15B 13/0418 (2013.01 - EP US); **Y10T 137/7761** (2015.04 - EP US)

Citation (search report)
See references of WO 2010130334A1

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

DOCDB simple family (publication)
DE 102009021103 A1 20101118; DK 2430319 T3 20130722; EP 2430319 A1 20120321; EP 2430319 B1 20130529; JP 2012526952 A 20121101; US 2011308642 A1 20111222; WO 2010130334 A1 20101118

DOCDB simple family (application)
DE 102009021103 A 20090513; DK 10717055 T 20100423; EP 10717055 A 20100423; EP 2010002501 W 20100423; JP 2012510129 A 20100423; US 201013138527 A 20100423