

Title (en)

Alarm, hazard warning assembly and method for detecting circuit faults

Title (de)

Gefahrenmelder, Gefahrenmeldeanlage und Verfahren zum Erkennen von Leitungsfehlern

Title (fr)

Alarme, installation d'alarme et procédé de reconnaissance d'erreurs de lignes de transmission

Publication

EP 2437228 A2 20120404 (DE)

Application

EP 11008014 A 20111004

Priority

DE 102010047227 A 20101004

Abstract (en)

The method involves setting power supply voltage for hazard detector (8), to measure first terminal voltage. The second terminal voltage of detector is measured by loading voltage source with defined current. A comparison voltage is detected by comparing first and second terminal voltages. The third terminal voltage of detector is measured when switch of connecting line (7) of detectors is closed, and is compared with comparison voltage. The switch is opened when third terminal voltage is below comparison voltage, to initiate operation of detector. Independent claims are included for the following: (1) hazard detector; and (2) short circuit disconnecting switch.

Abstract (de)

Die Erfindung betrifft eine Gefahrenmeldeanlage und einen Kurzschlusstrenner sowie Gefahrenmelder und weitere periphere Geräte mit einem integrierten Kurzschlusstrenner. Die Erfindung betrifft weiter ein Verfahren zum Erkennen von Leitungsfehlern in der Gefahrenmeldeanlage durch den Kurzschlusstrenner und die Zentrale, wobei Leitungsfehler durch den Vergleich von gemessenen Spannungswerten mit einer Vergleichspannung erkannt werden, die der Kurzschlusstrenner in Abhängigkeit seiner Einbauposition innerhalb einer Gefahrenmelderlinie selbst bestimmt.

IPC 8 full level

G08B 26/00 (2006.01)

CPC (source: EP)

G08B 26/005 (2013.01); **G08B 29/123** (2013.01)

Citation (applicant)

- DE 69514445 T2 20000706 - NOHMI BOSAI LTD [JP]
- DE 3624604 A1 19870205 - HOCHIKI CO [JP]
- EP 0347808 A1 19891227 - AICHER MAX
- EP 0347806 A1 19891227 - SIEMENS AG [DE]

Cited by

CN112689858A; US11367339B2; US11328580B2; EP3825973A1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

DOCDB simple family (publication)

DE 102010047227 B3 20120301; EP 2437228 A2 20120404; EP 2437228 A3 20120516; EP 2437228 B1 20160810

DOCDB simple family (application)

DE 102010047227 A 20101004; EP 11008014 A 20111004