

Title (en)
Elastic belt

Title (de)
Elastischer Gurt

Title (fr)
Ceinture élastique

Publication
EP 2449923 B1 20130828 (DE)

Application
EP 11008639 A 20111028

Priority
AT 6792010 U 20101105

Abstract (en)
[origin: EP2449923A1] The belt has a locking mechanism e.g. Velcro(RTM: Hook and loop fastener) and snap lock, for connecting both end parts. Maximum elastic elongation of the belt lies between 10 to 200 percentage. No or minimal contraction in width is carried out during the elastic elongation. Elongation force lies in a range between 5 and 50 Newton. Length of the belt lies between 800 and 1500 mm, and is adjusted by the locking mechanism. A fixing device i.e. hook and loop tape, is attached perpendicular to the belt.

IPC 8 full level
A47C 23/06 (2006.01); **A47C 31/11** (2006.01)

CPC (source: EP)
A47C 31/11 (2013.01)

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)
AT 11672 U2 20110315; AT 11672 U3 20110715; CY 1114670 T1 20161005; EP 2449923 A1 20120509; EP 2449923 B1 20130828;
ES 2435842 T3 20131223; HR P20131055 T1 20131220

DOCDB simple family (application)
AT 6792010 U 20101105; CY 131101059 T 20131127; EP 11008639 A 20111028; ES 11008639 T 20111028; HR P20131055 T 20131106