

Title (en)
Burglary resistant building termination

Title (de)
Gebäudeabschluss in einbruchhemmender Ausführung

Title (fr)
Fermeture de bâtiment de type anti-cambriolage

Publication
EP 2450519 B1 20130821 (DE)

Application
EP 11157827 A 20110311

Priority
EP 11157827 A 20110311

Abstract (en)
[origin: EP2450519A1] The termination (1) has a head element (30) projecting in a radial direction over a diameter of a bolt-like element so that a form-fit connection between a fastening element (7) and an inner frame profile (3) is formed relative to transmission of tensile force in cooperation with a through hole in the profile. The bolt like element, the head element and another head element (29) i.e. counter nut, form a rotational fixed unit so that the entire unit is rotated during manipulation of the latter head element. A distance between the head elements remains constant.

IPC 8 full level
E06B 5/11 (2006.01); **E04B 2/96** (2006.01)

CPC (source: EP)
E04B 2/967 (2013.01); **E06B 5/116** (2013.01)

Cited by
DE102014217348B4; EP3296482A1; NL2017459B1; EP2990561A1; DE102014217348A1; DE202015105953U1

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)
EP 2450519 A1 20120509; EP 2450519 B1 20130821; PL 2450519 T3 20140430

DOCDB simple family (application)
EP 11157827 A 20110311; PL 11157827 T 20110311