

Title (en)

Sewing machine and method for sewing a beginning of a seam with such a sewing machine

Title (de)

Nähmaschine sowie Verfahren zum Nähen eines Nahtanfangs mit einer derartigen Nähmaschine

Title (fr)

Machine à coudre et procédé destiné à coudre un début de couture à l'aide d'une telle machine à coudre

Publication

**EP 2453050 B1 20140402 (DE)**

Application

**EP 11186488 A 20111025**

Priority

DE 102010043906 A 20101115

Abstract (en)

[origin: EP2453050A1] The machine has needle bar (7) with sewing needle (8) that guides upper thread (9) by weight material. An upper yarn clamp (14) is arranged in supply-side upper thread course between gripper (10) and thread lever (18). An upper thread tension device (21) is arranged in supply-side upper thread path in front of upper yarn clamp. A thread pulling unit (24) provided between upper yarn clamp and thread lever is changeable between neutral and thread-pulling positions. The path of upper thread in thread-pulling position about thread path difference is set longer than in neutral position.

IPC 8 full level

**D05B 47/04** (2006.01)

CPC (source: EP KR)

**D05B 47/00** (2013.01 - KR); **D05B 47/04** (2013.01 - EP KR)

Cited by

EP3176296A1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

**EP 2453050 A1 20120516; EP 2453050 B1 20140402**; CN 102535038 A 20120704; CN 102535038 B 20150506;  
DE 102010043906 A1 20120516; KR 101862871 B1 20180530; KR 20120052161 A 20120523; TW 201245530 A 20121116;  
TW I498467 B 20150901

DOCDB simple family (application)

**EP 11186488 A 20111025**; CN 201110362200 A 20111115; DE 102010043906 A 20101115; KR 20110116720 A 20111110;  
TW 100141421 A 20111114