

Title (en)
INTERNAL COMBUSTION ENGINE WITH ECCENTRIC ROTATING CYLINDER AND PISTONS.

Title (de)
VERBRENNUNGSMOTOR MIT EXZENTRISCHEM ROTIERENDEM ZYLINDER UND KOLBEN

Title (fr)
MOTEUR À COMBUSTION INTERNE AVEC CYLINDRE ET PISTONS EN TOURNANT EXCENTRIQUEMENT.

Publication
EP 2462317 A2 20120613 (EN)

Application
EP 10762759 A 20100730

Priority
• IT RM20090432 A 20090807
• IT 2010000344 W 20100730

Abstract (en)
[origin: WO2011016072A2] The invention, relates to an internal combustion engine, comprising at least one cylinders/head group (1) and at least one pistons group (2), said groups rotating relatively to each other about a first rotation pin (A; B); said at least one cylinders/head group (1) has a first central hole (6), through which said first rotation pin (A; B) passes, and a first axis (9), offset with respect to said first central hole (6); said at least one pistons group (2) has a second central hole (7), through which said first rotation pin (A; B) passes, a second axis (12), offset with respect to said second central hole (7), and a first slot (10), through which said first axis (9) passes, set in a diametrically opposed position to said second axis (12) with respect to said second central hole (7); the offset distance of said first and second axis (9, 12) from a central axis passing through said first (6) and second (7) central hole is the same; said internal combustion engine being characterized in that it comprises a central nucleus (3; 30), having a third central hole (8), with a diameter smaller than said central hole (6, 7) diameters, and through which a second rotation pin (15, 15') passes, a second slot (11), through which said first axis (9) passes, and a third slot (13), through which said second axis (12) passes; in that said second pin (15; 15') has a section smaller than said first pin (A; B) section, integral with it and offset from its central axis; in that the rotation of said at least one cylinders/head group (1), said at least one pistons group (2) and said central nucleus (3; 30) around said first and second rotation pin (A; B, 15; 15') in said first, second and third holes (6, 7, 8) is eccentric and brought by the movement of said first and second axis (9, 12) within said slots (11,13).

IPC 8 full level
F01C 1/063 (2006.01)

CPC (source: EP)
F01C 1/063 (2013.01)

Citation (search report)
See references of WO 2011016072A2

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

DOCDB simple family (publication)
WO 2011016072 A2 20110210; WO 2011016072 A3 20111124; EP 2462317 A2 20120613; IT 1395233 B1 20120905;
IT RM20090432 A1 20110208

DOCDB simple family (application)
IT 2010000344 W 20100730; EP 10762759 A 20100730; IT RM20090432 A 20090807