

Title (en)

ROTARY SCREEN PRINTING DEVICE AND METHOD

Title (de)

ROTATIONSSIEBDRUCKVORRICHTUNG UND -VERFAHREN

Title (fr)

DISPOSITIF ET PROCÉDÉ DE SÉRIGRAPHIE ROTATIVE

Publication

EP 2464518 A1 20120620 (DE)

Application

EP 10747169 A 20100816

Priority

- DE 102009037332 A 20090814
- EP 2010005016 W 20100816

Abstract (en)

[origin: WO2011018243A1] The invention relates to a rotary screen printing device, comprising a printing cylinder (6) rotatably mounted around a printing cylinder axis (10), the cylinder jacket of the printing cylinder being formed at least in certain areas by a printing screen (8), an impression cylinder (4) rotatably mounted around an impression cylinder axis (11), and a squeegee (17) that can be moved relative to the cylinder jacket of the printing cylinder (6) and is arranged at least partially inside the printing cylinder (6) for pressing printing ink through the printing screen (8) onto a substrate (2) to be imprinted. At least one adjustment device is provided for adjusting a distance (15) between the printing cylinder axis (10) and the impression cylinder axis (11) and/or a radius of the printing cylinder (6) and/or the impression cylinder (4).

IPC 8 full level

B41F 15/08 (2006.01)

CPC (source: EP US)

B41F 15/0809 (2013.01 - EP US); **B41F 15/0872** (2013.01 - EP US); **B41F 15/38** (2013.01 - EP US); **B41F 15/42** (2013.01 - EP US);
B41F 15/46 (2013.01 - EP US)

Citation (search report)

See references of WO 2011018243A1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

DOCDB simple family (publication)

DE 102009037332 A1 20110217; CN 102625748 A 20120801; EP 2464518 A1 20120620; JP 2013501646 A 20130117;
US 2012204744 A1 20120816; WO 2011018243 A1 20110217

DOCDB simple family (application)

DE 102009037332 A 20090814; CN 201080042399 A 20100816; EP 10747169 A 20100816; EP 2010005016 W 20100816;
JP 2012524158 A 20100816; US 201013390196 A 20100816