

Title (en)

Hinge apparatus

Title (de)

Gelenkvorrichtung

Title (fr)

Appareil à charnière

Publication

EP 2466045 A2 20120620 (EN)

Application

EP 11193819 A 20111215

Priority

JP 2010282249 A 20101217

Abstract (en)

basal end portion of a force transmitter 81 is rotatably disposed in a second support shaft 74 rotatably connecting an internal link 72 to a body 3. A distal end portion of the force transmitter 81 is projected out of a guide hole 3g formed in a top plate 3b of the body 3. A pressing portion 81b is disposed in the projected distal end portion of the force transmitter 81. A receiver 83 is disposed in an end portion that is spaced from an instantaneous rotation center of a mounting member 4 when the mounting member 4 is positioned near a closed position. The pressing portion 81b is pressed against the receiver 83 by the torsion coil spring 82, thereby causing the mounting member 4 to be rotated toward the closed position.

IPC 8 full level

E05D 3/14 (2006.01); **E05D 11/10** (2006.01)

CPC (source: EP)

E05D 3/142 (2013.01); **E05D 11/1021** (2013.01); **E05F 1/1215** (2013.01); **E05D 7/0407** (2013.01); **E05D 7/0415** (2013.01); **E05D 7/125** (2013.01); **E05Y 2201/638** (2013.01); **E05Y 2800/268** (2013.01); **E05Y 2900/20** (2013.01)

Citation (applicant)

JP S60112973 A 19850619 - YOGOU SUMIKIN SANGYO KK

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

DOCDB simple family (publication)

EP 2466045 A2 20120620; **EP 2466045 A3 20141105**; CN 102536016 A 20120704; JP 2012127168 A 20120705; JP 5188565 B2 20130424

DOCDB simple family (application)

EP 11193819 A 20111215; CN 201110402988 A 20111207; JP 2010282249 A 20101217