

Title (en)
SOFT MAGNETIC FERRITIC CHROMIUM STEEL

Title (de)
WEICHMAGNETISCHER FERRITISCHER CHROMSTAHL

Title (fr)
ACIER CHROMÉ FERRITIQUE MAGNÉTIQUE DOUX

Publication
EP 2470682 A1 20120704 (DE)

Application
EP 10771635 A 20100823

Priority
• DE 102009038386 A 20090824
• EP 2010005150 W 20100823

Abstract (en)
[origin: WO2011023349A1] A soft magnetic ferritic chromium steel having at most 0.025% carbon, at most 0.02% nitrogen, 0.5 to 1.8% silicon, 0.30 to 1.5% manganese, 0.20 to 0.35% sulfur, 12.0 to 18.0% chromium, 0.05 to 0.8% copper, 0.5 to 3.0% molybdenum, 0.02 to 0.35% niobium, 0.4 to 1.2% vanadium, up to 0.6% titanium, 0.001 to 0.02% aluminum, up to 0.2% calcium, 0.01 to 1.0% nickel, 0.01 to 0.4% cobalt, and up to 0.004% boron is suitable as a corrosion-resistant, low-burr micro-machinable material having a low coercive force, in particular for functional magnetic elements, for example for producing magnetic valves, motor vehicle injection systems, control valves, magnetic field shields in plasma chambers and physical devices.

IPC 8 full level
C22C 38/04 (2006.01); **C21D 1/26** (2006.01); **C22C 38/02** (2006.01); **C22C 38/42** (2006.01); **C22C 38/44** (2006.01); **C22C 38/46** (2006.01); **C22C 38/48** (2006.01); **C22C 38/52** (2006.01); **C22C 38/60** (2006.01)

CPC (source: EP)
C22C 38/02 (2013.01); **C22C 38/04** (2013.01); **C22C 38/42** (2013.01); **C22C 38/44** (2013.01); **C22C 38/46** (2013.01); **C22C 38/48** (2013.01); **C22C 38/52** (2013.01); **C22C 38/60** (2013.01); **C21D 1/26** (2013.01); **C21D 2211/005** (2013.01)

Citation (search report)
See references of WO 2011023349A1

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

DOCDB simple family (publication)
DE 102009038386 A1 20110303; **DE 102009038386 A8 20110622**; EP 2470682 A1 20120704; EP 2470682 B1 20141224;
WO 2011023349 A1 20110303

DOCDB simple family (application)
DE 102009038386 A 20090824; EP 10771635 A 20100823; EP 2010005150 W 20100823