

Title (en)

METHODOLOGY FOR THE REMOVAL OF INORGANIC COMPONENTS FROM BIOMASS OF AGRO/FOREST/URBAN ORIGIN AND FROM LOW-QUALITY COAL SUCH AS PEAT, LIGNITE, SUB-BITUMINOUS AND BITUMINOUS COALS

Title (de)

VERFAHREN ZUR ENTFERNUNG VON ANORGANISCHEN BESTANDTEILEN AUS BIOMASSE LANDWIRTSCHAFTLICHEN/FORSTLICHEN/STÄDTISCHEN URSPRUNGS UND AUS GERINGWERTIGER KOHLE WIE ETWA TORF-, BRAUN-, FETT- UND WEICHKOHLE

Title (fr)

MÉTHODOLOGIE POUR ÉLIMINER DES COMPOSANTS INORGANIQUES ISSUS DE LA BIOMASSE D'ORIGINE AGRICOLE/FORESTIÈRE/URBAINE ET ISSUS DU CHARBON BASSE QUALITÉ TEL QUE LA TOURBE, LA LIGNITE, LES CHARBONS SOUS-BITUMINEUX ET BITUMINEUX

Publication

EP 2475750 A1 20120718 (EN)

Application

EP 10759834 A 20100909

Priority

- GR 20090100486 A 20090910
- GR 20090100487 A 20090910
- GR 20100100012 A 20100111
- EP 2010063268 W 20100909

Abstract (en)

[origin: WO2011029885A1] A methodology for the removal of the harmful components of ash from urban/industrial wastes and sludges from the sewage treatment plants is invented. The harmful components are alkaline metals, chlorine, sulphur, zinc, lead, and chromium. They are removed before the thermochemical conversion and therefore the corrosion problems, scaling/deposition, ash agglomeration, dioxin and furan emissions, alkaline metal, chlorine, sulphur emissions are minimized if not diminished. The emissions of heavy metals such as zinc, lead, copper, and chromium are reduced. The removal is achieved with prepyrolysis/pregasification at 250-320 °C for 5 min to 2 h of urban/industrial wastes and sludges from the sewage treatment plants. Then the prepyrolysed/pregasified sample is washed with a 0.5%-5% weight basis aqueous calcium acetate and/or magnesium acetate and/or aluminum acetate solution. These acetate salts can be mixed in a proportion of 0% to 100% to form an active salt which is used for the preparation of the aqueous solution. Otherwise, they can be used separately to prepare separate solutions for successive extractions with the same results. The proportions used and the use or not of successive extractions depend on the kind and on the composition of the initial material as well as on the desired properties of the material after treatment. Any kind tap water from a public water supply system, spring, etc. can be used for the preparation of aqueous solution. The solid-to-liquid ratio is 33g/L to 600 g/L, the temperature varies from 13°C to 95°C, and treatment time is between 5 min to 2.

IPC 8 full level

C10L 5/44 (2006.01); **C10B 53/02** (2006.01); **C10L 9/08** (2006.01); **C10L 9/10** (2006.01)

CPC (source: EP US)

C10B 53/00 (2013.01 - US); **C10B 57/14** (2013.01 - US); **C10G 1/00** (2013.01 - EP US); **C10G 1/02** (2013.01 - EP US); **C10L 5/46** (2013.01 - EP US); **C10L 5/48** (2013.01 - EP US); **C10L 9/08** (2013.01 - EP US); **C10L 9/083** (2013.01 - EP US); **C10L 9/10** (2013.01 - EP US); **C10G 2300/1003** (2013.01 - EP US); **C10G 2300/201** (2013.01 - EP US); **Y02E 50/10** (2013.01 - US); **Y02E 50/30** (2013.01 - US)

Citation (search report)

See references of WO 2011029891A1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

DOCDB simple family (publication)

WO 2011029885 A1 20110317; CA 2773508 A1 20110317; CA 2773509 A1 20110317; CA 2773509 C 20171212; EP 2475750 A1 20120718; EP 2475750 B1 20210310; EP 2475751 A1 20120718; US 10041015 B2 20180807; US 2012151835 A1 20120621; US 2012160659 A1 20120628; US 9809773 B2 20171107; WO 2011029891 A1 20110317

DOCDB simple family (application)

EP 2010063262 W 20100909; CA 2773508 A 20100909; CA 2773509 A 20100909; EP 10759834 A 20100909; EP 10760949 A 20100909; EP 2010063268 W 20100909; US 201013394137 A 20100909; US 201013394140 A 20100909