

Title (en)
OPENING SEQUENCE CONTROL DEVICE OF A DOUBLE-LEAFED DOOR

Title (de)
ÖFFNUNGSFOLGESTEUERUNGSEINRICHTUNG EINER ZWEIFLÜGELIGEN TÜR

Title (fr)
DISPOSITIF D'ASSERVISSEMENT D'OUVERTURE D'UNE PORTE À DEUX BATTANTS

Publication
EP 2476845 B1 20181003 (DE)

Application
EP 12000152 A 20120112

Priority
DE 102011008419 A 20110112

Abstract (en)
[origin: EP2476845A2] The device has drive unit (11) that has fixing arm (11b), stop arm (11a) and return spring (11f) which resets stop arm from secondary swivel position to primary swivel position. A hinge element (11g) combines the stop arm and fixing arm which is fixed to a fixed leaf (1) and a movable leaf (2). The fixing arm is mounted at the movable leaf such that stop arm is arranged vertical to door axis boundary edge or end face of fixed leaf in primary swivel position, and is parallel to door axis boundary edge or end face of fixed leaf in secondary swivel position.

IPC 8 full level
E05F 5/12 (2006.01)

CPC (source: EP)
E05F 5/12 (2013.01); **E05Y 2600/41** (2013.01); **E05Y 2600/412** (2013.01)

Cited by
CN111904247A; EP2662520A3

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)
EP 2476845 A2 20120718; **EP 2476845 A3 20140910**; **EP 2476845 B1 20181003**; DE 102011008419 A1 20120712;
DE 102011008419 A8 20130117; DE 102011008419 A8 20130328; DE 102011008419 A9 20121122

DOCDB simple family (application)
EP 12000152 A 20120112; DE 102011008419 A 20110112