

Title (en)  
PIXEL CIRCUIT AND DISPLAY DEVICE

Title (de)  
PIXELSCHALTUNG UND ANZEIGEVORRICHTUNG

Title (fr)  
CIRCUIT DE PIXEL ET DISPOSITIF D'AFFICHAGE

Publication  
**EP 2477180 A1 20120718 (EN)**

Application  
**EP 10813550 A 20100524**

Priority  
• JP 2009206473 A 20090907  
• JP 2010058743 W 20100524

Abstract (en)  
A display device that realizes a reduction in power consumption without causing deterioration of an aperture is provided. A liquid crystal capacitor element (Clc) is interposed between a pixel electrode (20) and a counter electrode (80). A counter voltage (Vcom) is applied to the counter electrode (80). The pixel electrode (20), one terminals of a first switch circuit (22) and a second switch circuit (23), and a first terminal of a second transistor (T2) form an internal node (N1). The other terminals of the first switch circuit (22) is connected to the source line (SL). The other terminal of the second switch circuit (23) is connected to the voltage supply line (VSL) and is configured by a series circuit of transistors (T1 and T3). A control terminal of the transistor (T1), a second terminal of the transistor (T2), and one terminal of a boost capacitor element (Cbst) form an output node (N2). The other terminal of the boost capacitor element (Cbst), the control terminal of the transistor (T2), and the control terminal of the transistor (T3) are connected to a boost line (BST), a reference line (REF), and a selecting line (SEL), respectively.

IPC 8 full level  
**G09G 3/36** (2006.01); **G02F 1/133** (2006.01); **G02F 1/1368** (2006.01); **G09G 3/20** (2006.01)

CPC (source: EP US)  
**G09G 3/3659** (2013.01 - EP US); **G09G 2300/0852** (2013.01 - EP US)

Designated contracting state (EPC)  
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

DOCDB simple family (publication)  
**EP 2477180 A1 20120718**; **EP 2477180 A4 20130320**; BR 112012005043 A2 20190924; CN 102498510 A 20120613; CN 102498510 B 20141008; IN 3122CHN2012 A 20150529; JP 5346380 B2 20131120; JP WO2011027599 A1 20130204; RU 2487422 C1 20130710; US 2012154365 A1 20120621; US 8384835 B2 20130226; WO 2011027599 A1 20110310

DOCDB simple family (application)  
**EP 10813550 A 20100524**; BR 112012005043 A 20100524; CN 201080039890 A 20100524; IN 3122CHN2012 A 20120404; JP 2010058743 W 20100524; JP 2011529839 A 20100524; RU 2012113631 A 20100524; US 201013392893 A 20100524