

## Title (en)

Disc-shaped recording medium, recording method, and disc drive apparatus

## Title (de)

Plattenförmiges Aufzeichnungsmedium, Aufzeichnungsverfahren und Plattenlaufwerk

## Title (fr)

Support d'enregistrement en forme de disque, procédé d'enregistrement et lecteur de disque

## Publication

**EP 2479755 A1 20120725 (EN)**

## Application

**EP 12164329 A 20030604**

## Priority

- EP 03736025 A 20030604
- JP 2002170266 A 20020611

## Abstract (en)

It is an object of the present invention to improve reliability of defect management. This is obtained by providing a plurality of management data areas each including a defect management area typically in a lead-in zone of a disc inner-side region enclosed by a circumference having a predetermined radius on a disc-shaped recording medium. In addition, the plurality of the defect management areas are placed at locations, which are separated from each other in the radial direction of the disc-shaped recording medium, sandwiching a recording/reproduction condition adjustment area OPC having a relatively large size. If information stored in one defect management area is found to be different to information stored in another defect management area, then the information in the defect management areas is made uniform by copying the information stored in an earlier defect management area to a later defect management area in a predetermined priority order.

## IPC 8 full level

**G11B 20/12** (2006.01); **G11B 7/004** (2006.01); **G11B 7/0045** (2006.01); **G11B 7/007** (2006.01); **G11B 11/00** (2006.01); **G11B 19/04** (2006.01); **G11B 20/18** (2006.01); **G11B 27/24** (2006.01)

## CPC (source: EP KR US)

**G11B 7/004** (2013.01 - KR); **G11B 7/007** (2013.01 - KR); **G11B 7/00736** (2013.01 - EP US); **G11B 19/04** (2013.01 - EP US); **G11B 20/00347** (2013.01 - EP US); **G11B 20/00949** (2013.01 - EP US); **G11B 20/10** (2013.01 - KR); **G11B 20/12** (2013.01 - KR); **G11B 20/1251** (2013.01 - EP US); **G11B 20/1252** (2013.01 - EP US); **G11B 20/1833** (2013.01 - EP US); **G11B 20/1883** (2013.01 - EP US); **G11B 27/24** (2013.01 - EP US); **G11B 20/18** (2013.01 - EP US); **G11B 2020/1222** (2013.01 - EP US); **G11B 2020/1268** (2013.01 - EP US); **G11B 2020/1272** (2013.01 - EP US); **G11B 2020/1453** (2013.01 - EP US); **G11B 2020/1836** (2013.01 - EP US); **G11B 2220/20** (2013.01 - EP US); **G11B 2220/2541** (2013.01 - EP US)

## Citation (search report)

- [E] WO 03063144 A2 20030731 - MATSUSHITA ELECTRIC IND CO LTD [JP]
- [A] EP 0478323 A2 19920401 - IBM [US]
- [XA] ECMA: STANDARDIZING INFORMATION AND COMMUNICATION SYSTEMS: "Standard ECMA-274, 2nd edition: Data Interchange on 120mm optical disk using +RW format - Capacity 3,0 Gbytes and 6,0 Gbytes", STANDARD ECMA-274, XX, XX, no. 272, 1 June 1999 (1999-06-01), pages 1 - 105, XP002186788

## Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PT RO SE SI SK TR

## DOCDB simple family (publication)

**EP 1513150 A1 20050309**; **EP 1513150 A4 20100217**; **EP 1513150 B1 20121205**; AU 2003242029 A1 20031222; AU 2003242029 B2 20081113; CN 101877227 A 20101103; CN 101877227 B 20140611; CN 1554092 A 20041208; CN 1554092 B 20120704; EP 2479755 A1 20120725; ES 2399888 T3 20130404; HK 1075117 A1 20051202; JP 2004014088 A 20040115; KR 20050004767 A 20050112; MX PA04000827 A 20040514; RU 2004103974 A 20050227; RU 2316828 C2 20080210; TW 200405273 A 20040401; TW I254280 B 20060501; US 2005083740 A1 20050421; US 7313062 B2 20071225; WO 03105150 A1 20031218

## DOCDB simple family (application)

**EP 03736025 A 20030604**; AU 2003242029 A 20030604; CN 03801017 A 20030604; CN 201010109942 A 20030604; EP 12164329 A 20030604; ES 03736025 T 20030604; HK 05107400 A 20050823; JP 0307077 W 20030604; JP 2002170266 A 20020611; KR 20047002066 A 20030604; MX PA04000827 A 20030604; RU 2004103974 A 20030604; TW 92115080 A 20030603; US 48628204 A 20040209