

Title (en)
GEOMAGNETISM DETECTION DEVICE

Title (de)
VORRICHTUNG ZUR GEOMAGNETISMUSERKENNUNG

Title (fr)
DISPOSITIF DE DÉTECTION DE GÉOMAGNÉTISME

Publication
EP 2482033 B1 20151021 (EN)

Application
EP 10818790 A 20100922

Priority
• JP 2009221715 A 20090926
• JP 2010066344 W 20100922

Abstract (en)
[origin: US2012078562A1] A controller includes a calibration unit, an offset error correcting unit, an operation unit, and the like. The calibration unit obtains a reference point of an output of a magnetic sensor, and performs offset correction. The offset error correcting unit is capable of performing operation processing for both the correction of a major offset error and the correction of a minor offset error by using a radius (the magnitude of a geomagnetic vector) of a virtual circle or a virtual sphere, appropriately and easily correcting the offset error with a small amount of operation, and reducing the burden to the controller.

IPC 8 full level
G01C 17/38 (2006.01); **G01R 33/02** (2006.01)

CPC (source: EP US)
G01C 17/28 (2013.01 - EP US); **G01C 17/38** (2013.01 - EP US); **G01R 33/0035** (2013.01 - EP US); **G01R 33/0206** (2013.01 - EP US); **G01V 3/081** (2013.01 - EP US); **G01V 3/40** (2013.01 - EP US)

Cited by
FR2992735A1; WO2014001470A1

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

DOCDB simple family (publication)
US 2012078562 A1 20120329; CN 102510994 A 20120620; CN 102510994 B 20140108; EP 2482033 A1 20120801; EP 2482033 A4 20140101; EP 2482033 B1 20151021; JP 5469670 B2 20140416; JP WO2011037117 A1 20130221; WO 2011037117 A1 20110331

DOCDB simple family (application)
US 201113314091 A 20111207; CN 201080040796 A 20100922; EP 10818790 A 20100922; JP 2010066344 W 20100922; JP 2011532998 A 20100922