

Title (en)

CONVEYOR DEVICE AND METHOD FOR OPERATING A CONVEYOR DEVICE

Title (de)

FÖRDEREINRICHTUNG UND VERFAHREN ZUM BETRIEB EINER FÖRDEREINRICHTUNG

Title (fr)

DISPOSITIF D'ACHEMINEMENT ET PROCÉDÉ POUR FAIRE FONCTIONNER UN DISPOSITIF D'ACHEMINEMENT

Publication

EP 2483184 A1 20120808 (DE)

Application

EP 10776521 A 20101001

Priority

- AT 15612009 A 20091002
- AT 17242009 A 20091030
- AT 2010000365 W 20101001

Abstract (en)

[origin: WO2011038439A1] The invention relates to a conveyance device (1) comprising several drives (2, 2a..2c) arranged successively in the direction of conveyance (z, z1, z2) and used to transport objects (22a..22d) at an actual speed. Said conveyance device (1) comprises means for determining a desired position of an object (22a..22d) using a desired speed of the drives (2, 2a..2c) and the time which has elapsed after passing a reference point (p), or using a desired path which is predefined by the drives (2, 2a..2c) and which is traversed after passing a reference point (p). Said conveyance device (1) comprises a control/regulation element for controlling or regulating a desired distance between two objects (22a..22d) using the mentioned desired position. According to the invention, said conveyance device (1) also comprises at least one sensor (17, 18, 23) which is provided for detecting a first range (A) and a second range (B), the second detection range (B) being arranged in the direction of conveyance (z, z1, z2) behind the first detection range (A) at a first distance (x, x1, x2). Said conveyance device (1) also comprises means for testing whether at least one distance (x, x1, x2) is maintained between two objects (22a..22d) transported by said conveyance device (1) using a signal emitted by the at least one sensor (17, 18, 23) in such a manner that a positive result is signalled when the objects (22a..22d) pass both detection ranges (A, B), the two detected ranges being at least free of objects (22a..22d) for a short time or at least partially covered such that at least the first distance (x, x1, x2) can be determined. The invention also relates to a method for testing whether the first distance (x, x1, x2) between two objects (22a..22d) transported by the conveyance device (1) is maintained.

IPC 8 full level

B65G 43/10 (2006.01); **B65G 47/26** (2006.01)

CPC (source: EP)

B65G 43/10 (2013.01); **B65G 47/261** (2013.01)

Citation (search report)

See references of WO 2011038440A1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

WO 2011038439 A1 20110407; AT 508864 A1 20110415; AT 508864 B1 20120415; AT 508865 A1 20110415; AT 508865 B1 20120415; AT 509818 A1 20111115; CN 102648137 A 20120822; CN 102648137 B 20160525; DE 202010018479 U1 20170110; EP 2483183 A1 20120808; EP 2483184 A1 20120808; WO 2011038440 A1 20110407

DOCDB simple family (application)

AT 2010000364 W 20101001; AT 15612009 A 20091002; AT 17242009 A 20091030; AT 2010000365 W 20101001; AT 5862011 A 20110426; CN 201080052495 A 20101001; DE 202010018479 U 20101001; EP 10776520 A 20101001; EP 10776521 A 20101001