

Title (en)

Jack-socket for providing an electric connection

Title (de)

Klinkenbuchse zur Herstellung einer elektrischen Steckverbindung

Title (fr)

Prise-jack pour réaliser une connexion électrique enfichable

Publication

EP 2485344 B1 20151125 (DE)

Application

EP 12000272 A 20120118

Priority

DE 102011010155 A 20110202

Abstract (en)

[origin: EP2485344A1] The jack socket has plug housing (10) having receiving space into which plug shaft of jack plug is inserted. The housing has several contacts (20,30) having terminal portions (21,31,41,51,61) parallel to longitudinal central axis (12) of receiving space of plug housing. The tip contact point and tip-contact switch pad comprising region of contact portion (32) of the tip contact has a longitudinal extension which is transverse to longitudinal central axis. The tip contact point is removed from free end (34) of tip contact to which contact portion of tip contact is connected. The jack socket has plug housing having receiving space into which plug shaft of the jack plug from an insertion end with respect to longitudinal center axis of the receiving space is inserted. The housing has sleeve contact (20) with contact portion for contacting contact sleeve of jack plug. A tip contact (30) has contact portion which is deflected during insertion of jack plug from contact tip from initial position into end position and is contactable in the inserted state of jack plug from contact tip at tip contact point. A tip-switching contact has contact portion which rests in initial position of contact portion of tip contact at tip-contact switch pad of contact portion of tip contact and from which contact portion of tip contact in end position of contact portion of tip contact is lifted. The terminal portions parallel to the longitudinal central axis of the receiving space of the plug housing. The tip contact point and tip-switching contact pad comprising region of contact portion of the tip contact has a longitudinal extension which is transverse to the longitudinal central axis of the receiving space of the plug housing. The tip contact point and the tip-switch contact pad of the contact portion of the tip contact are spaced apart in transverse to the longitudinal central axis of the receiving space of the plug housing. The tip contact point is removed from the free end of the tip contact to which the contact portion of the tip contact is connected.

IPC 8 full level

H01R 13/703 (2006.01); **H01R 24/58** (2011.01); **H01R 105/00** (2006.01)

CPC (source: EP US)

H01R 13/7033 (2013.01 - EP US); **H01R 24/58** (2013.01 - EP US); **H01R 2105/00** (2013.01 - EP US)

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

EP 2485344 A1 20120808; **EP 2485344 B1 20151125**; CN 102629711 A 20120808; CN 102629711 B 20161005; DE 102011010155 A1 20120802; ES 2560609 T3 20160222; JP 2012160452 A 20120823; JP 5572173 B2 20140813; PL 2485344 T3 20160531; US 2012196487 A1 20120802; US 8435080 B2 20130507

DOCDB simple family (application)

EP 12000272 A 20120118; CN 201210076496 A 20120201; DE 102011010155 A 20110202; ES 12000272 T 20120118; JP 2012018870 A 20120131; PL 12000272 T 20120118; US 201213363636 A 20120201