

Title (en)

Hoist unit and load-bearing medium for such a unit

Title (de)

AUFZUGSANLAGE UND TRAGMITTEL FÜR EINE SOLCHE ANLAGE

Title (fr)

Installation d'ascenseur et moyen de support pour une telle installation

Publication

**EP 2488436 B1 20160113 (DE)**

Application

**EP 10761015 A 20101006**

Priority

- EP 09173069 A 20091014
- EP 2010064902 W 20101006
- EP 10761015 A 20101006

Abstract (en)

[origin: WO2011045215A1] The invention relates to an elevator system having a suspension and a suspension for supporting and/or moving at least one elevator car (3) in an elevator system (1), wherein the suspension (12) can be guided and driven at least by means of a sheave (4), in particular a traction sheave (4.1) of a drive machine (2) of an elevator system (1), and the suspension (12) comprises a body (15) made of a polymer and at least one tie beam (22) extending in the longitudinal direction of the suspension (12) and embedded in the body (15) and made of wires (42) and is present as a cord or rope. A thickest wire (43) having the greatest wire diameter d in the tie beam (22) comprises a bending stress sb in a range from sb = 350N/mm<sup>2</sup> to 900N/mm<sup>2</sup> when bending the tie beam (18) about a least bending radius r, and wherein the bending stress sb results as a function of the elastic modulus E and the diameter d of the thickest wire (26), according to the following equation: sb = (d\*E)/2r, wherein the suspension (12) is run about a smallest pulley having a least pulley diameter D in the elevator system (1), the pulley diameter D thereof corresponding to no more than two times the least bending radius r: D = 2r.

IPC 8 full level

**B66B 7/06** (2006.01); **D07B 1/16** (2006.01)

CPC (source: EP KR US)

**B66B 7/062** (2013.01 - EP US); **B66B 11/04** (2013.01 - KR); **D07B 1/0673** (2013.01 - EP US); **D07B 1/162** (2013.01 - EP US); **D07B 1/22** (2013.01 - EP US); **D07B 2201/2037** (2013.01 - EP US); **D07B 2401/206** (2013.01 - EP US); **D07B 2501/2007** (2013.01 - EP US)

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

**WO 2011045215 A1 20110421**; AU 2010305872 A1 20120503; BR 112012008407 A2 20160329; CA 2777541 A1 20110421; CL 2012000935 A1 20120803; CN 102574665 A 20120711; CN 102574665 B 20151125; EP 2488436 A1 20120822; EP 2488436 B1 20160113; ES 2567783 T3 20160426; HK 1174320 A1 20130607; KR 20120083907 A 20120726; MX 2012004353 A 20120907; MY 183948 A 20210317; RU 2012117956 A 20131120; US 2012211310 A1 20120823; ZA 201202550 B 20130626

DOCDB simple family (application)

**EP 2010064902 W 20101006**; AU 2010305872 A 20101006; BR 112012008407 A 20101006; CA 2777541 A 20101006; CL 2012000935 A 20120412; CN 201080046011 A 20101006; EP 10761015 A 20101006; ES 10761015 T 20101006; HK 13101678 A 20130206; KR 20127012092 A 20101006; MX 2012004353 A 20101006; MY PI2012001546 A 20101006; RU 2012117956 A 20101006; US 201013502273 A 20101006; ZA 201202550 A 20120410