

Title (en)

Spacer and sub-assembly for separating the levers of a shedding machine, machine including such a sub-assembly and installation method

Title (de)

Abstandhalter und Unterelement zur Trennung von Hebeln einer Fachbildungsmaschine, Maschine, die ein solches Unterelement umfasst und entsprechendes Montageverfahren

Title (fr)

Entretoise et sous-ensemble de séparation des leviers d'une machine de formation de la foule, machine comprenant un tel sous-ensemble et procédé de montage

Publication

EP 2492381 B1 20130911 (FR)

Application

EP 12156886 A 20120224

Priority

FR 1151577 A 20110225

Abstract (en)

[origin: EP2492381A1] The spacer (32) has a first housing (329), which borders a central opening (322) for receiving and maintaining components of an axial abutment. A second housing (337) receives a seal. A first support element (326) is supported against a portion of a frame of a shedding machine. A second support element (327) is in contact with a fixed part of the machine. A band (338) is extended between the support elements, where width (I338) of the band parallel to a central axis (X32) of the central opening is constant. Independent claims are also included for the following: (1) a shedding machine (2) a method for mounting a shedding machine.

IPC 8 full level

D03C 1/14 (2006.01)

CPC (source: EP)

D03C 1/14 (2013.01)

Cited by

EP3162933A1; EP3272918A1; FR3054245A1; CN107641874A; US10433135B2; US10287712B2; FR3043096A1; EP4095296A1; FR3123366A1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

EP 2492381 A1 20120829; EP 2492381 B1 20130911; CN 102650085 A 20120829; CN 102650085 B 20150826; FR 2972008 A1 20120831; FR 2972008 B1 20130329

DOCDB simple family (application)

EP 12156886 A 20120224; CN 201210044848 A 20120224; FR 1151577 A 20110225