

Title (en)
MULTI-BLADE FAN FOR CENTRIFUGAL BLOWER

Title (de)
LÜFTER MIT MEHREREN BLÄTTERN FÜR EIN ZENTRIFUGALGEBLÄSE

Title (fr)
VENTILATEUR À AUBES MULTIPLES POUR SOUFFLANTE CENTRIFUGE

Publication
EP 2503157 A1 20120926 (EN)

Application
EP 10831457 A 20101104

Priority
• JP 2009264094 A 20091119
• JP 2010196893 A 20100902
• JP 2010069575 W 20101104

Abstract (en)
Disclosed is a multi-blade fan for a centrifugal blower, the multi-blade fan having a plurality of annularly-disposed blades and being characterized in that at least the number of blades (Z), the inner/outer diameter ratio, which is defined as the ratio (D1/D2) between the diameter (D1) of the circle inscribing the blades and the diameter (D2) of the circle circumscribing the blades, the angle of inclination (a degrees) of each blade, which is defined as the angle between a line connecting the position of said blade on the inscribed circle and the position thereof on the circumscribed circle and a line extending radially from the center of the inscribed circle and passing through said position on the inscribed circle, and the tongue clearance ratio, which is defined as the ratio (S/D2) between the tongue clearance (S) and the diameter (D2); of the circumscribed circle are all within optimal ranges ($30 \leq Z \leq 55$; $0.72 \leq D1/D2 \leq 0.86$; $15 \leq a \leq 48$; and $0.09 \leq S/D2 \leq 0.15$). Thus, it is possible to design a multi-blade fan for a centrifugal blower that produces little noise by determining the optimal ranges for parameters that were found to be effective and combining those optimal ranges for use.

IPC 8 full level
F04D 29/30 (2006.01); **F04D 29/44** (2006.01); **F04D 29/66** (2006.01)

CPC (source: EP)
F04D 29/281 (2013.01); **F04D 29/30** (2013.01); **F04D 29/422** (2013.01); **F04D 29/441** (2013.01); **F05D 2250/52** (2013.01)

Citation (search report)
See references of WO 2011062062A1

Cited by
FR3069896A1; FR3069895A1; US9885361B2; FR3074236A1; FR3074237A1; US10718351B2; WO2019102101A1; WO2019025710A1; EP2991206B1

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)
EP 2503157 A1 20120926; CN 102667173 A 20120912; JP 2011127586 A 20110630; WO 2011062062 A1 20110526

DOCDB simple family (application)
EP 10831457 A 20101104; CN 201080051918 A 20101104; JP 2010069575 W 20101104; JP 2010196893 A 20100902