

Title (en)
LIGHTING APPARATUS

Title (de)
LEUCHTVORRICHTUNG

Title (fr)
DISPOSITIF D'ÉCLAIRAGE

Publication
EP 2521875 A1 20121114 (DE)

Application
EP 11723344 A 20110513

Priority
• DE 102010029227 A 20100521
• EP 2011057737 W 20110513

Abstract (en)
[origin: WO2011144522A1] The lighting apparatus (1;13) has a light source substrate (2) to whose front face (2a) at least one semiconductor light source (3), in particular a light-emitting diode (3), is fitted, and the rear face (2b) of which is fitted to an electrically conductive mount, wherein, in addition to the light source substrate (2), at least two electrically conductive contact pins (9) are passed through the mount, and the contact pins (9) are electrically connected to the at least one semiconductor light source (2), and wherein the contact pins (9) are each introduced into an electrically insulating sleeve (8), and the respective sleeve (8) is inserted into an associated cutout (7) in the mount.

IPC 8 full level
F21K 99/00 (2010.01)

CPC (source: EP US)
F21K 9/20 (2016.07 - EP US); **F21V 23/06** (2013.01 - EP US); **F21V 23/001** (2013.01 - EP US); **F21Y 2105/10** (2016.07 - EP US); **F21Y 2115/10** (2016.07 - EP US); **H01L 2224/48091** (2013.01 - EP US); **H01L 2224/48472** (2013.01 - EP US); **H05K 1/0306** (2013.01 - EP US); **H05K 3/0061** (2013.01 - EP US); **H05K 2201/10106** (2013.01 - EP US); **Y10T 29/49002** (2015.01 - EP US)

Citation (search report)
See references of WO 2011144522A1

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)
DE 102010029227 A1 20111124; CN 102906486 A 20130130; EP 2521875 A1 20121114; US 2013063946 A1 20130314; WO 2011144522 A1 20111124

DOCDB simple family (application)
DE 102010029227 A 20100521; CN 201180024754 A 20110513; EP 11723344 A 20110513; EP 2011057737 W 20110513; US 201113699306 A 20110513