

Title (en)
HEAT EXCHANGER

Title (de)
WÄRMETAUSCHER

Title (fr)
ECHANGEUR DE CHALEUR

Publication
EP 2532998 A4 20150107 (EN)

Application
EP 10845251 A 20101029

Priority
• JP 2010022997 A 20100204
• JP 2010069768 W 20101029

Abstract (en)
[origin: EP2532998A1] A heat exchanger wherein the pipe member is formed in a single stage to reduce the height of the heat exchanger in the thickness direction thereof to thereby enable the heat exchanger to be satisfactorily mounted below the floor of an automobile and wherein the pipe member is prevented from being broken by a stone flipped up by the automobile during running thereof. A heat exchanger comprises: fin members (3) formed as corrugated fins and having engagement recesses (8) formed in curved sections (6); and a pipe member (1) formed by connecting straight pipe sections (2) by U-shaped bend sections (5), the straight pipe sections (2) being arranged by means of the fin members (3). In a state in which the straight pipe sections (2) are engaged with the engagement recesses (8) of the fin members (3), the outer diameter of the pipe member (1) is in the range of 8 to 12 mm, and the facing distance (17) between the fin members (3) is in the range of 0.5 to 5.0 mm. Also, the height of the protrusion of the fin members (3) is set to a value which is less than or equal to 11 mm and which, when the facing distance (17) is within the range of 0.5 to 5.0 mm, satisfies the formula of $y \neq 2.46x - 0.29$ (y: (the height of the protrusion of the fin members (3) from the surface of the pipe member (1))/(the facing distance (17) between curved top sections (15)), x: the facing distance (17) between the curved top sections (15)).

IPC 8 full level
F28F 1/30 (2006.01); **F28D 1/047** (2006.01); **F28F 1/10** (2006.01); **F28F 1/12** (2006.01); **F28F 1/32** (2006.01); **F28F 9/00** (2006.01)

CPC (source: EP US)
F28D 1/0477 (2013.01 - EP US); **F28F 1/10** (2013.01 - US); **F28F 1/126** (2013.01 - EP US); **F28F 1/32** (2013.01 - EP US); **F28F 9/002** (2013.01 - EP US); **F28F 2215/12** (2013.01 - EP US)

Citation (search report)
• [A] EP 1696196 A1 20060830 - USUI KOKUSAI SANGYO KK [JP]
• [A] US 3275072 A 19660927 - SUCHOMEL RAYMOND F
• [A] US 3407874 A 19681029 - GIER JR JOHN R
• [A] EP 0271319 A2 19880615 - PEERLESS OF AMERICA [US]
• [A] EP 0881448 A2 19981202 - SHOWA ALUMINUM CORP [JP]
• See references of WO 2011096120A1

Cited by
US10082343B2; WO2016008427A1

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)
EP 2532998 A1 20121212; **EP 2532998 A4 20150107**; **EP 2532998 B1 20160330**; JP 2011163567 A 20110825; JP 5393514 B2 20140122; KR 101698966 B1 20170123; KR 20120115267 A 20121017; US 2013118724 A1 20130516; WO 2011096120 A1 20110811

DOCDB simple family (application)
EP 10845251 A 20101029; JP 2010022997 A 20100204; JP 2010069768 W 20101029; KR 20127015384 A 20101029; US 201013577343 A 20101029