

Title (en)
TIGHTNESS-INDICATING TUBE FITTING

Title (de)
ROHRVERSCHRAUBUNG MIT DICHTIGKEITSANZEIGE

Title (fr)
RACCORD DE TUYAUTERIE INDIQUANT L'ÉTANCHÉITÉ

Publication
EP 2535631 A4 20160824 (EN)

Application
EP 10845838 A 20100223

Priority
• KR 20100012762 A 20100211
• KR 2010001102 W 20100223

Abstract (en)
[origin: EP2535631A1] The present invention relates to a tube fitting which is designed to be easily checked by visual inspection as to whether the nut tightening reaches a reference value. The tube fitting comprises a tube inserted into a body, at least one ferrule disposed around the tube, and a nut tightened onto the body to deform the ferrule for providing a seal between the body and the tube. If the nut is tightened on the body to a reference value, a check ring is detached from the body by a pressing force of the nut such that the coupling state of the nut can be checked.

IPC 8 full level
F16L 19/10 (2006.01)

CPC (source: EP US)
F16L 19/103 (2013.01 - EP US); **F16L 2201/10** (2013.01 - EP US)

Citation (search report)
• [XAY] US 4475748 A 19841009 - EKMAN KJELL R [CH]
• [XYI] US 2002148128 A1 20021017 - WILLIAMS PETER C [US], et al
• [Y] US 2001015556 A1 20010823 - JOHNSTON LONNIE E [US]
• See references of WO 2011099667A1

Cited by
US10302598B2; US10774961B2; WO2015187958A1

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

DOCDB simple family (publication)
EP 2535631 A1 20121219; EP 2535631 A4 20160824; EP 2535631 B1 20181003; ES 2695586 T3 20190109; JP 2013519848 A 20130530; JP 5654616 B2 20150114; KR 100987334 B1 20101012; US 2012313367 A1 20121213; US 9528640 B2 20161227; WO 2011099667 A1 20110818

DOCDB simple family (application)
EP 10845838 A 20100223; ES 10845838 T 20100223; JP 2012552783 A 20100223; KR 2010001102 W 20100223; KR 20100012762 A 20100211; US 201013577597 A 20100223