

Title (en)

DEVICE FOR AN AT LEAST PARTIALLY REMOVABLE ANCHOR AND METHOD FOR AT LEAST PARTIALLY REMOVING AN ANCHOR

Title (de)

VORRICHTUNG FÜR EINEN ZUMINDEST TEILWEISE AUSBAUBAREN ANKER UND VERFAHREN ZUM ZUMINDEST TEILWEISEN AUSBAU EINES ANKERS

Title (fr)

DISPOSITIF POUR UN ANCRAJE AU MOINS PARTIELLEMENT DÉMONTABLE, ET PROCÉDÉ DE DÉMONTAGE AU MOINS PARTIEL D'UN ANCRAJE

Publication

EP 2550404 A2 20130130 (DE)

Application

EP 10711318 A 20100325

Priority

CH 2010000086 W 20100325

Abstract (en)

[origin: WO2011116483A2] The device for an at least partially removable anchor comprises at least one tension member (9) that can be pre-loaded and an induction coil (16) surrounding the tension member for disconnecting the tension member at a disconnection point (12) by inductive heating. The induction coil (16) is arranged on a carrier pipe (15), which is sealed (17, 20) on the side of the disconnection point (12) facing the part (7) of the tension member that can be pre-loaded. The area between the induction coil (16) and the disconnection point (12) is free from an electrically conducting metal pipe. In order to at least partially remove the anchor, the tension member (9) is pre-loaded during the heating process with a force that corresponds to at least 10%, preferably at least 25%, and especially preferably at least 50% of the fracture force of the tension member at 0 degrees Celsius.

IPC 8 full level

E02D 5/76 (2006.01)

CPC (source: EP)

E02D 5/765 (2013.01)

Citation (search report)

See references of WO 2011116483A2

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

DOCDB simple family (publication)

WO 2011116483 A2 20110929; WO 2011116483 A3 20120308; EP 2550404 A2 20130130; EP 2550404 B1 20170712;
EP 2998447 A1 20160323; EP 2998447 B1 20171004

DOCDB simple family (application)

CH 2010000086 W 20100325; EP 10711318 A 20100325; EP 15192785 A 20100325