

Title (en)
VOLTAGE DETECTOR, ABNORMALITY DETECTION DEVICE, NON-CONTACT POWER TRANSFER DEVICE, NON-CONTACT POWER RECEIVER DEVICE, AND VEHICLE

Title (de)
SPANNUNGSEDETEKTOR, VORRICHTUNG ZUR ERKENNUNG VON ANOMALITÄTEN, KONTAKTFREIE LEISTUNGSÜBERTRAGUNGSVORRICHTUNG, KONTAKTFREIE LEISTUNGSEMPFANGSVORRICHTUNG UND FAHRZEUG

Title (fr)
DÉTECTEUR DE TENSION, DISPOSITIF DE DÉTECTION D'ANOMALIES, DISPOSITIF DE TRANSFERT D'ÉNERGIE SANS CONTACT, DISPOSITIF RÉCEPTEUR D'ÉNERGIE SANS CONTACT ET VÉHICULE

Publication
EP 2555375 A8 20130327 (EN)

Application
EP 10848974 A 20100527

Priority
• JP 2010078236 A 20100330
• JP 2010058974 W 20100527

Abstract (en)
[origin: EP2555375A1] A voltage detector for detecting a voltage generated in a second resonant coil (110; 240) that is disposed to face a first resonant coil (240; 110) and that performs at least one of electric power transmission and electric power reception to and from the first resonant coil (240; 110) in a contactless manner by means of electromagnetic resonance includes: a first high-impedance element (510) having one end connected to one end of the second resonant coil (110; 240); a second high-impedance element (520) having one end connected to the other end of the second resonant coil (110; 240); a low-impedance element (550) connected between the other end of the first high-impedance element (510) and the other end of the second high-impedance element (520) and having an impedance smaller than each of those of the first and second high-impedance elements (510, 520); and an output terminal (560) for outputting a signal associated with a voltage applied across the low-impedance element (550). In this way, in the contactless power supply system employing the resonance method, the malfunction in the resonant coil is detected while suppressing an influence over the resonance state between the resonant coils and suppressing increase of cost.

IPC 8 full level
B60L 11/18 (2006.01); **B60L 50/16** (2019.01); **H02J 17/00** (2006.01); **G01R 31/72** (2020.01)

CPC (source: EP US)
B60L 3/00 (2013.01 - EP US); **B60L 3/0023** (2013.01 - EP US); **B60L 50/16** (2019.01 - EP US); **B60L 50/40** (2019.01 - EP US); **B60L 50/60** (2019.01 - EP US); **B60L 53/122** (2019.01 - EP US); **B60L 53/126** (2019.01 - EP US); **B60L 53/36** (2019.01 - EP US); **B60L 58/12** (2019.01 - EP US); **B60L 58/40** (2019.01 - EP US); **G06F 12/00** (2013.01 - US); **H02J 7/00** (2013.01 - US); **H02J 7/0048** (2020.01 - EP US); **H02J 7/007192** (2020.01 - US); **H02J 7/02** (2013.01 - EP US); **H02J 50/12** (2016.02 - EP US); **H02J 50/70** (2016.02 - EP US); **H02J 50/90** (2016.02 - EP US); **H02M 3/33561** (2013.01 - EP US); **B60L 2210/10** (2013.01 - EP US); **B60L 2210/30** (2013.01 - EP US); **B60L 2210/40** (2013.01 - EP US); **B60L 2240/36** (2013.01 - EP US); **B60L 2240/527** (2013.01 - EP US); **B60L 2240/662** (2013.01 - EP US); **B60L 2250/10** (2013.01 - EP US); **G01R 31/72** (2020.01 - EP US); **H02J 7/00034** (2020.01 - EP US); **H02J 2310/48** (2020.01 - EP US); **Y02T 10/70** (2013.01 - EP US); **Y02T 10/7072** (2013.01 - EP US); **Y02T 10/72** (2013.01 - EP US); **Y02T 90/12** (2013.01 - EP US); **Y02T 90/14** (2013.01 - EP US); **Y02T 90/16** (2013.01 - EP US); **Y02T 90/40** (2013.01 - US)

Citation (search report)
See references of WO 2011121800A1

Cited by
DE102017107310A1; CN109843636A; DE102021005551A1; WO2015173614A1; US11117479B2; WO2018069542A1

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

DOCDB simple family (publication)
EP 2555375 A1 20130206; **EP 2555375 A4 20150826**; **EP 2555375 A8 20130327**; **EP 2555375 B1 20180912**; CN 102971939 A 20130313; CN 102971939 B 20151125; JP 2011211854 A 20111020; JP 5290228 B2 20130918; US 2013009650 A1 20130110; US 8907680 B2 20141209; WO 2011121800 A1 20111006

DOCDB simple family (application)
EP 10848974 A 20100527; CN 201080065934 A 20100527; JP 2010058974 W 20100527; JP 2010078236 A 20100330; US 201013576525 A 20100527