

Title (en)
Bridging of a floor recess

Title (de)
Überbrückung einer Bodenaussparung

Title (fr)
Enjambement d'un évidement au sol

Publication
EP 2565147 B1 20140806 (DE)

Application
EP 12181941 A 20120828

Priority
DE 102011112206 A 20110902

Abstract (en)
[origin: EP2565147A1] The device (30) has a plate (31) movably arranged within a bottom recess (20) such that the plate is moved from a position into another position by lowering a lifting platform by a chassis testing device (14) that is coupled with rails (12). The plate covers the bottom recess in the former position. The bottom recess is released in the latter position for retaining the chassis testing device. The plate is supported on a beam grill, and a resetting mechanism is designed as a spring loaded toggle or articulated lever mechanism. A guide device comprises multiple guide surfaces.

IPC 8 full level
B66F 7/28 (2006.01); **B66F 17/00** (2006.01)

CPC (source: EP)
B66F 7/28 (2013.01); **B66F 17/00** (2013.01)

Cited by
US9610666B2; WO2014029529A1

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)
EP 2565147 A1 20130306; EP 2565147 B1 20140806; DE 102011112206 A1 20130307; DK 2565147 T3 20140929

DOCDB simple family (application)
EP 12181941 A 20120828; DE 102011112206 A 20110902; DK 12181941 T 20120828