

Title (en)
Method and device for broadband analysis of systems and substances

Title (de)
Verfahren und Vorrichtung zur Breitbandanalyse von Systemen und Substanzen

Title (fr)
Procédé et dispositif d'analyse à large bande des systèmes et substances

Publication
EP 2565654 A2 20130306 (EN)

Application
EP 12182280 A 20120829

Priority
EE P201100054 A 20110830

Abstract (en)
A method and device for high speed broadband testing of systems and substances using a binary, spectrally sparse sequence (SSS) as a periodic excitation waveform. The sequences with controllable frequency and magnitude spectra content are designed by component manipulation method or by edge manipulation method. The excitation waveform is typically pre-calculated, and kept in waveform memory, from where it is shifted out into digital to physical quantity converter (DQC). The sparse spectrum of the SSS makes it easy to create plenty of uncorrelated frequency sets with adjacent, but sufficiently different frequencies to form multi-path test systems, where all the paths can be measured simultaneously. The response of the sample under test (SUT) is sampled and the complex transfer function is calculated directly or indirectly via Impulse Response by Discrete Fourier Transform technique and its derivatives. The sequence bit interval and sampling interval have a predetermined ratio.

IPC 8 full level
A61B 5/053 (2021.01); **G01R 27/28** (2006.01); **G01N 22/00** (2006.01); **G01R 31/28** (2006.01); **G06F 1/02** (2006.01)

CPC (source: EP US)
G01R 27/28 (2013.01 - EP US); **G01R 31/2841** (2013.01 - EP US); **G06F 1/03** (2013.01 - EP US)

Citation (applicant)

- US 4093988 A 19780606 - SCOTT PAUL F
- WO 2007054700 A1 20070518 - UNIV SOUTHAMPTON [GB], et al
- US 7194317 B2 20070320 - KOTHARE SIMONE L [US], et al
- EP 1786322 B1 20091028 - TALLINN UNIVERSITY OF TECHNOLO [EE]
- WO 2004052198 A1 20040624 - TALLINN TECHNICAL UNIVERSITY [EE], et al
- WO 2009138093 A1 20091119 - TALLINN UNIVERSITY OF TECHNOLO [EE], et al
- WO 2007054700 A1 20070518 - UNIV SOUTHAMPTON [GB], et al
- US 5051916 A 19910924 - BENSON RICHARD A [US]
- US 7194317 B2 20070320 - KOTHARE SIMONE L [US], et al
- J. SCHOUKENS ET AL.: "Survey of Excitation Signals for FFT Based Signal Analyzers", IEEE TRANSACTIONS ON INSTRUMENTATION AND MEASUREMENT, vol. 37, no. 3, September 1988 (1988-09-01), XP055099667, DOI: doi:10.1109/19.7453
- R.PINTELON; J. SCHOUKENS: "Design of Excitation Signals", 2001, WILEY-IEEE PRESS, article "System Identification: A Frequency Domain Approach", pages: 115 - 138
- E. VAN DER OUDERAA; J.SCHOUKENS; J. RENNEBOOG: "Peak Factor Minimization of Input and output Signals of Linear Systems", IEEE TRANS. ON INSTRUMENTATION AND MEASUREMENT, vol. 37, no. 2, June 1988 (1988-06-01), pages 207 - 212, XP055099665, DOI: doi:10.1109/19.6053
- MANFRED F. SCHROEDER.: "Synthesis of low peak factor signals and binary sequences with low autocorrelation", IEEE TRANS. INFORMATION THEORY, vol. IT-16, January 1970 (1970-01-01), pages 85 - 89, XP055099664, DOI: doi:10.1109/TIT.1970.1054411
- A. VAN DEN BOS.: "A new method for synthesis of low-peak-factor signals", IEEE TRANSACTIONS ON ACOUSTICS, SPEECH, AND SIGNAL PROCESSING, vol. ASSP-35, no. 1, January 1987 (1987-01-01), pages 120 - 122
- S.BOYD.: "Multitone signals with low crest factor", IEEE TRANSACTIONS ON CIRCUITS AND SYSTEMS, vol. CAS-33, no. 10, October 1986 (1986-10-01), pages 1018 - 1022, XP000857183, DOI: doi:10.1109/TCS.1986.1085837
- U.PLIQUETT.: "Bioimpedance: A Review for Food Processing", FOOD ENGINEERING REVIEW, vol. 2, 2010, pages 74 - 94
- S. GAWAD ET AL.: "Review of Scientific Instruments", vol. 78, May 2007, AMERICAN INSTITUTE OF PHYSICS, article "Impedance spectroscopy using maximum length sequences: Application to single cell analysis", pages: 054301
- KUHMBERG, A.; LAND, R.; MIN, M.; PARVE, T.: "PWM based lock-in bioimpedance measurement unit for implantable medical devices", PROCEEDINGS OF THE XVII IMEKO WORLD CONGRESS: XVII IMEKO WORLD CONGRESS, DUBROVNIK, 22 June 2003 (2003-06-22), pages 1710 - 1713
- MIN, M.; MARTENS, O.; PARVE, T.: "Lock-in measurement of bio-impedance variations", MEASUREMENT, vol. 27, no. 1, 2000, pages 21 - 28, XP004244780, DOI: doi:10.1016/S0263-2241(99)00048-2
- D.D. RIFE; J. VANDERKOOY: "Transfer Function Measurement with Maximum-Length Sequences", J.AUDIO ENG. SOC., vol. 37, no. 6, 1989, pages 419 - 443
- T. NACKE ET AL.: "ICEBI 2007, IFMBE Proceedings", vol. 17, 2007, SPRINGER-VERLAG, article "A new hard- and software concept for impedance spectroscopy analysers for broadband process measurements", pages: 194 - 197
- MIN, M.; GIANNITSIS, A. T.; LAND, R.; CAHILL, B. P.; PLIQUETT, U.; NACKE, T.; FRENSE, D.; GASTROCK, G.; BECKMANN, D.: "Proceedings of World Congress 2009 in Medical Physics and Biomedical Engineering: World Congress 2009 in Medical Physics and Biomedical Engineering", 2009, SPRINGER VERLAG, article "Comparison of rectangular wave excitations in broad band impedance spectroscopy for microfluidic applications", pages: 85 - 88
- Y. YANG; M. KANG; Y.LU; J. WANG; J. YUE; Z. GAO: "Design of a wideband excitation source for fast bioimpedance spectroscopy", MEAS. SCI. TECHNOL., vol. 22, 2011, pages 8

Cited by
FR3051915A1

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)
BA ME

DOCDB simple family (publication)

EP 2565654 A2 20130306; EP 2565654 A3 20170517; EP 2565654 B1 20240403; EE 05668 B1 20130815; EE 201100054 A 20130415;
US 10698023 B2 20200630; US 2013054178 A1 20130228

DOCDB simple family (application)

EP 12182280 A 20120829; EE P201100054 A 20110830; US 201213598955 A 20120830