

Title (en)

Clock barrel assembly with reduced core diameter

Title (de)

Uhren-Federgehäuse mit reduziertem Durchmesser des Bundes

Title (fr)

Ensemble barillet d'horlogerie à diamètre de bonde réduit

Publication

EP 2570863 B1 20171108 (FR)

Application

EP 11181353 A 20110915

Priority

EP 11181353 A 20110915

Abstract (en)

[origin: EP2570863A1] The assembly (1) has a driving spring (2) mounted between a drum (3) and a reception surface (5) of a core (4). Maximum radius of the core with respect to a pivoting axis (D) is less than ten times the maximum thickness of the spring. An arbor (18) comprises a ratchet holder (81) placed between an end shoulder (85) and a bearing (84), and provided with another bearing to drive a ratchet (12). The ratchet holder directly or indirectly limits the play of the drum relative to a bearing surface of the core that borders the reception surface. An independent claim is also included for a movement.

IPC 8 full level

G04B 1/14 (2006.01); **G04B 1/16** (2006.01)

CPC (source: EP US)

G04B 1/145 (2013.01 - US); **G04B 1/16** (2013.01 - EP US); **G04B 1/165** (2013.01 - US)

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

EP 2570863 A1 20130320; EP 2570863 B1 20171108; CN 103797423 A 20140514; CN 103797423 B 20160928; IN 2742CHN2014 A 20150703; JP 2014526688 A 20141006; JP 5807121 B2 20151110; KR 101625771 B1 20160530; KR 20140059863 A 20140516; RU 2557403 C1 20150720; US 2014204719 A1 20140724; US 9158282 B2 20151013; WO 2013037864 A1 20130321

DOCDB simple family (application)

EP 11181353 A 20110915; CN 201280045227 A 20120913; EP 2012067902 W 20120913; IN 2742CHN2014 A 20140410; JP 2014530205 A 20120913; KR 20147010022 A 20120913; RU 2014114786 A 20120913; US 201214241714 A 20120913