

Title (en)
START DEVICE AND METHOD FOR ASSEMBLING A STOPPER FOR THE AXIAL DISPLACEMENT OF THE PINION ON A SHAFT OF A STARTING DEVICE WITH A CAP.

Title (de)
STARTVORRICHTUNG UND VERFAHREN ZUM ZUSAMMENBAUEN EINES ANSCHLAGS ZUM VERHINDERN DER AXIALEN BEWEGUNG EINES AUF EINER WELLE ANGEORDNETES RITZELS EINER STARTVORRICHTUNG MIT EINEM VERSCHLUSS.

Title (fr)
DISPOSITIF DE DÉMARRAGE ET PROCÉDÉ POUR ASSEMBLER UN ARRÊT AFIN D'EMPÊCHER LE DÉPLACEMENT AXIAL D'UN PIGNON PLACÉ SUR UN ARBRE D'UN DÉMARREUR AVEC UNE CAPSULE DE FERMETURE.

Publication
EP 2588745 B1 20200226 (DE)

Application
EP 11729109 A 20110629

Priority
• DE 102010030727 A 20100630
• EP 2011060870 W 20110629

Abstract (en)
[origin: WO2012001025A2] A starting device (16) having a drive shaft (19) and having a hollow shaft (13) which is at least displaceable on the drive shaft (19) and which has an opening (20) on the end side, having a closure (53) which closes off the opening (20) on the end side, wherein the closure (53) engages over a projection (76) arranged on the hollow shaft (13), is characterized in that a ring (80) has an engaging-over contour (86) which grasps at least a part of the engaging-over contour (74) of the closure (53).

IPC 8 full level
F02N 15/06 (2006.01); **F16L 55/115** (2006.01)

CPC (source: EP)
F02N 15/065 (2013.01); **F02N 2250/08** (2013.01)

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)
DE 102010030727 A1 20120105; DE 102010030727 B4 20160331; CN 103154500 A 20130612; CN 103154500 B 20160316;
EP 2588745 A2 20130508; EP 2588745 B1 20200226; HU E049005 T2 20200928; WO 2012001025 A2 20120105; WO 2012001025 A3 20120223

DOCDB simple family (application)
DE 102010030727 A 20100630; CN 201180032154 A 20110629; EP 11729109 A 20110629; EP 2011060870 W 20110629;
HU E11729109 A 20110629