

Title (en)
DRUM-TYPE WASHING MACHINE

Title (de)
TROMMELWASCHMASCHINE

Title (fr)
LAVE-LINGE DU TYPE À TAMBOUR

Publication
EP 2597187 A1 20130529 (EN)

Application
EP 12749536 A 20120220

Priority
• JP 2011036743 A 20110223
• JP 2012001116 W 20120220

Abstract (en)
A drum-type washing machine according to the present invention is adapted to have a mode for selecting a detection axis along which vibration values in a water tank (42) in three-dimensional directions, which have been detected by a vibration detector (78), indicate a maximum value, and for restarting a spin-drying operation when the vibration value detected along this detection axis exceeds a first threshold value defined for each rotation-speed range of a rotary drum (43) but is less than a second threshold value, in spin-drying processes. With this structure, the drum-type washing machine can early detect imbalance abnormalities and can safely stop running.

IPC 8 full level
D06F 33/48 (2020.01); **D06F 37/20** (2006.01)

CPC (source: EP US)
D06F 33/48 (2020.02 - EP US); **D06F 2103/24** (2020.02 - EP US); **D06F 2103/26** (2020.02 - EP US); **D06F 2105/62** (2020.02 - EP US)

Cited by
EP4368764A1; EP3701074A4; US10000877B2; US11149372B2; WO2019124989A1; US11396723B2; EP3348697A1; WO2018130396A1; US10000876B2; US10494750B2; US11306425B2; US11326296B2; US11814773B2; US11905639B2; US12084801B2

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)
EP 2597187 A1 20130529; EP 2597187 A4 20140827; EP 2597187 B1 20171213; CN 103080404 A 20130501; CN 103080404 B 20150708; JP 2012170686 A 20120910; SI 2597187 T1 20180330; WO 2012114716 A1 20120830

DOCDB simple family (application)
EP 12749536 A 20120220; CN 201280002571 A 20120220; JP 2011036743 A 20110223; JP 2012001116 W 20120220; SI 201231209 T 20120220